

# BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
19 October 2000 (19.10.2000)

PCT

(10) International Publication Number  
**WO 00/60995 A3**

(51) International Patent Classification<sup>7</sup>: **A61B 17/04**

(21) International Application Number: **PCT/US00/09290**

(22) International Filing Date: **7 April 2000 (07.04.2000)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:  
**60/128,690 9 April 1999 (09.04.1999) US**

(71) Applicant: **EVALVE, INC. [US/US]; 2761 Fair Oaks, Redwood City, CA 94063 (US).**

(72) Inventors: **DEEM, Mark, E.; 216 B Palo Alto Avenue, Mountain View, CA 94041 (US). GIFFORD, Hansen,**


**S., III; 3180 Woodside Road, Woodside, CA 94062 (US). DIECK, Martin, S.; 21105 Hazelbrook Drive, Cupertino, CA 95014 (US). FANN, James, I-Lin; 65 Prado Court, Portola Valley, CA 94028 (US). ST. GOAR, Frederick, G.; 2 Frederick Court, Menlo Park, CA 94025 (US). MARTIN, Brian, B.; 315 Alder Road, Boulder Creek, CA 95006 (US). FAN, Sylvia, Wen-Chin; 3868 21st Street, Apt. 2, San Francisco, CA 94114 (US). GOLDFARB, Eric, A.; 2822 Emerson Street, Palo Alto, CA 94306 (US). DELL, Kent, D.; 1131 Grand Street, Redwood City, CA 94061 (US). POWELL, Ferolyn, T.; 55 Caselli Avenue, San Francisco, CA 94114 (US).**

(74) Agents: **HESLIN, James, M. et al.; Townsend and Townsend and Crew LLP, 8th Floor, Two Embarcadero Center, San Francisco, CA 94111 (US).**

(81) Designated States (*national*): **AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,**

[Continued on next page]

(54) Title: **METHODS AND APPARATUS FOR CARDIAC VALVE REPAIR**



(57) Abstract: The methods, devices, and systems are provided for performing endovascular repair of atrioventricular and other cardiac valves in the heart. Regurgitation of an atrioventricular valve, particularly a mitral valve, can be repaired by modifying a tissue structure selected from the valve leaflets, the valve annulus, the valve chordae, and the papillary muscles. These structures may be modified by suturing, stapling, snaring, or shortening, using interventional tools (30, 36, 56) which are introduced to a heart chamber. Preferably, the tissue structures will be temporarily modified prior to permanent modification. For example, opposed valve leaflets may be temporarily grasped and held into position prior to permanent attachment.

WO 00/60995 A3



IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,  
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,  
UG, UZ, VN, YU, ZA, ZW.

Published:

— With international search report.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:

12 April 2001

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US00/09290

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) :A61B 17/04  
US CL :606/150

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 606/139, 142, 144, 150, 151; 623/2.11

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WEST

Search Terms: valve, leaflet, vasculature, catheter, coapt, ventricular, suture

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,716,367 A (KOIKE et al.) 10 February 1998, whole document.	65-67, 71, 72, 76, 77, 79, 80, 87
X,P	WO 00/03759 A (KUEHN et al.) 27 January 2000, whole document.	87-90



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means	
*P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

26 JULY 2000

Date of mailing of the international search report

02 NOV 2000

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

JULIAN W. WOO

Telephone No. (703) 308-0421



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: <b>A61B</b>	<b>A2</b>	(11) International Publication Number: <b>WO 00/60995</b> (43) International Publication Date: 19 October 2000 (19.10.2000)
(21) International Application Number: PCT/US00/09290 (22) International Filing Date: 07 April 2000 (07.04.2000) (30) Priority Data: 60/128,690 09 April 1999 (09.04.1999) US (60) Parent Application or Grant EVALVE, INC. [/]; (). DEEM, Mark, E. [/]; (). GIFFORD, Hansen, S., III [/]; (). DIECK, Martin, S. [/]; (). FANN, James, I-Lin [/]; (). ST. GOAR, Frederick, G. [/]; (). MARTIN, Brian, B. [/]; (). FAN, Sylvia, Wen-Chin [/]; (). GOLDFARB, Eric, A. [/]; (). DELL, Kent, D. [/]; (). POWELL, Ferolyn, T. [/]; (). HESLIN, James, M. ; ().	<b>Published</b>	
(54) Title: METHODS AND APPARATUS FOR CARDIAC VALVE REPAIR (54) Titre: PROCEDE ET DISPOSITIF DE REPARATION DE VALVULE CARDIAQUE  (57) Abstract  The methods, devices, and systems are provided for performing endovascular repair of atrioventricular and other cardiac valves in the heart. Regurgitation of an atrioventricular valve, particularly a mitral valve, can be repaired by modifying a tissue structure selected from the valve leaflets, the valve annulus, the valve chordae, and the papillary muscles. These structures may be modified by suturing, stapling, snaring, or shortening, using interventional tools which are introduced to a heart chamber. Preferably, the tissue structures will be temporarily modified prior to permanent modification. For example, opposed valve leaflets may be temporarily grasped and held into position prior to permanent attachment.  (57) Abrégé  L'invention concerne des procédés, dispositifs et systèmes d'exécution d'une réparation endovasculaire d'une valvule auriculo-ventriculaire et d'autres valvules cardiaques, dans le coeur. Il est possible de réparer la régurgitation d'une valvule auriculo-ventriculaire, notamment d'une valvule mitrale, en modifiant une structure tissulaire choisie à partir des valves, anneau et petits cordages d'une valvule, et des piliers du coeur. On peut modifier ces structures au moyen de sutures, agrafes, anses, ou raccourcissements, à l'aide d'outils introduits dans la cavité cardiaque. De préférence, on modifie temporairement ces structures tissulaires, avant de procéder à leur modification permanente. Par exemple on peut saisir et maintenir en position temporaire des valves de valvules, avant de les fixer de façon permanente.		



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>A61B</b>		(11) International Publication Number: <b>WO 00/60995</b>
<b>A2</b>		(43) International Publication Date: 19 October 2000 (19.10.00)
(21) International Application Number: PCT/US00/09290		(74) Agents: HESLIN, James, M. et al.; Townsend and Townsend and Crew LLP, 8th Floor, Two Embarcadero Center, San Francisco, CA 94111 (US).
(22) International Filing Date: 7 April 2000 (07.04.00)		
(30) Priority Data: 60/128,690 9 April 1999 (09.04.99) US		
(71) Applicant: EVALVE, INC. [US/US]; 2761 Fair Oaks, Redwood City, CA 94063 (US).		
(72) Inventors: DEEM, Mark, E.; 216 B Palo Alto Avenue, Mountain View, CA 94041 (US). GIFFORD, Hansen, S., III; 3180 Woodside Road, Woodside, CA 94062 (US). DIECK, Martin, S.; 21105 Hazelbrook Drive, Cupertino, CA 95014 (US). FANN, James, I-Lin; 65 Prado Court, Portola Valley, CA 94028 (US). ST. GOAR, Frederick, G.; 2 Frederick Court, Menlo Park, CA 94025 (US). MARTIN, Brian, B.; 315 Alder Road, Boulder Creek, CA 95006 (US). FAN, Sylvia, Wen-Chin; 3868 21st Street, Apt. 2, San Francisco, CA 94114 (US). GOLDFARB, Eric, A.; 2822 Emerson Street, Palo Alto, CA 94306 (US). DELL, Kent, D.; 1131 Grand Street, Redwood City, CA 94061 (US). POWELL, Ferolyn, T.; 55 Caselli Avenue, San Francisco, CA 94114 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
		Published Without international search report and to be republished upon receipt of that report.

(54) Title: METHODS AND APPARATUS FOR CARDIAC VALVE REPAIR

(57) Abstract

The methods, devices, and systems are provided for performing endovascular repair of atrioventricular and other cardiac valves in the heart. Regurgitation of an atrioventricular valve, particularly a mitral valve, can be repaired by modifying a tissue structure selected from the valve leaflets, the valve annulus, the valve chordae, and the papillary muscles. These structures may be modified by suturing, stapling, snaring, or shortening, using interventional tools which are introduced to a heart chamber. Preferably, the tissue structures will be temporarily modified prior to permanent modification. For example, opposed valve leaflets may be temporarily grasped and held into position prior to permanent attachment.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**Description**

5

10

15

20

25

30

35

40

45

50

55

5

## METHODS AND APPARATUS FOR CARDIAC VALVE REPAIR

10

### CROSS-REFERENCES TO RELATED APPLICATIONS

This application claims the benefit of prior provisional application no.

- 5 60/128,690, filed on April 9, 1999 under 37 CFR §1.78(a). The full disclosure of the prior provisional application is hereby incorporated herein by reference.

15

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

20

- 15 The present invention relates generally to medical methods, devices, and systems. In particular, the present invention relates to methods, devices, and systems for the endovascular or minimally invasive surgical repair of the atrioventricular valves of the heart, particularly the mitral valve.

25

- 20 Mitral valve regurgitation is characterized by retrograde flow from the left ventricle of a heart through an incompetent mitral valve into the left atrium. During a normal cycle of heart contraction (systole), the mitral valve acts as a check valve to prevent flow of oxygenated blood back into the left atrium. In this way, the oxygenated blood is pumped into the aorta through the aortic valve. Regurgitation of the valve can significantly decrease the pumping efficiency of the heart, placing the patient at risk of severe, progressive heart failure.

35

- 30 Mitral valve regurgitation can result from a number of different mechanical defects in the mitral valve. The valve leaflets, the valve chordae which connect the leaflets to the papillary muscles, or the papillary muscles themselves may be damaged or otherwise dysfunctional. Commonly, the valve annulus may be damaged, dilated, or weakened limiting the ability of the mitral valve to close adequately against the high pressures of the left ventricle.

40

- 45 The most common treatments for mitral valve regurgitation rely on valve replacement or strengthening of the valve annulus by implanting a mechanical support ring or other structure. The latter is generally referred to as valve annuloplasty. A recent technique for mitral valve repair which relies on suturing adjacent segments of the opposed valve leaflets together is referred to as the "bow-tie" or "edge-to-edge" technique. While all these techniques can be very effective, they usually rely on open

50

55

heart surgery where the patient's chest is opened, typically via a sternotomy, and the patient placed on cardiopulmonary bypass. The need to both open the chest and place the patient on bypass is traumatic and has associated morbidity.

For these reasons, it would be desirable to provide alternative and additional methods, devices, and systems for performing the repair of mitral and other cardiac valves, particularly the tricuspid valve which is the other atrioventricular valve. Such methods, devices, and systems should preferably not require open chest access and be capable of being performed endovascularly, i.e., using devices which are advanced to the heart from a point in the patient's vasculature remote from the heart. Still more preferably, the methods, devices, and systems should not require that the heart be bypassed, although the methods, devices, and systems should be useful with patients who are bypassed and/or whose heart may be temporarily stopped by drugs or other techniques. At least some of these objectives will be met by the inventions described hereinbelow.

## 2. Description of the Background Art

Minimally invasive and percutaneous techniques for coapting and modifying mitral valve leaflets to treat mitral valve regurgitation are described in WO 98/35638; WO 99/00059; WO 99/01377; and WO 00/03759.

Dec and Fuster (1994) N. Engl. J. Med. 331:1564-1575 and Alvarez et al. (1996) J. Thorac. Cardiovasc. Surg. 112:238-247 are review articles discussing the nature of and treatments for dilated cardiomyopathy.

Maisano et al. (1998) Eur. J. Cardiothorac. Surg. 13:240-246; Fucci et al. (1995) Eur. J. Cardiothorac. Surg. 9:621-627; and Umana et al. (1998) Ann. Thorac. Surg. 66:1640-1646, describe open surgical procedures for performing "edge-to-edge" or "bow-tie" mitral valve repair where edges of the opposed valve leaflets are sutured together to lessen regurgitation.

Mitral valve annuloplasty is described in the following publications. Bach and Bolling (1996) Am. J. Cardiol. 78:966-969; Kameda et al. (1996) Ann. Thorac. Surg. 61:1829-1832; Bach and Bolling (1995) Am. Heart J. 129:1165-1170; and Bolling et al. (1995) 109:676-683. Linear segmental annuloplasty for mitral valve repair is described in Ricchi et al. (1997) Ann. Thorac. Surg. 63:1805-1806. Tricuspid valve annuloplasty is described in McCarthy and Cosgrove (1997) Ann. Thorac. Surg. 64:267-268; Tager et al.

(1998) Am. J. Cardiol. 81:1013-1016; and Abe et al. (1989) Ann. Thorac. Surg. 48:670-676.

Percutaneous transluminal cardiac repair procedures are described in Park et al. (1978) Circulation 58:600-608; Uchida et al. (1991) Am. Heart J. 121: 1221-1224; and Ali Khan et al. (1991) Cathet. Cardiovasc. Diagn. 23:257-262.

Endovascular cardiac valve replacement is described in U.S. Patent Nos. 5,840,081; 5,411,552; 5,554,185; 5,332,402; 4,994,077; and 4,056,854. See also U.S. Patent No. 3,671,979 which describes a catheter for temporary placement of an artificial heart valve.

Other percutaneous and endovascular cardiac repair procedures are described in U.S. Patent Nos. 4,917,089; 4,484,579; and 3,874,338; and WO 91/01689.

Thoracoscopic and other minimally invasive heart valve repair and replacement procedures are described in U.S. Patent Nos. 5,855,614; 5,829,447; 5,823,956; 5,797,960; 5,769,812; and 5,718,725.

#### SUMMARY OF THE INVENTION

The present invention provides methods, devices, and systems for the endovascular repair of cardiac valves, particularly the atrioventricular valves which inhibit back flow of blood from a heart ventricle during contraction (systole), most particularly the mitral valve between the left atrium and the left ventricle. By "endovascular," it is meant that the procedure(s) of the present invention are performed with interventional tools and supporting catheters and other equipment introduced to the heart chambers from the patient's arterial or venous vasculature remote from the heart. The interventional tools and other equipment may be introduced percutaneously, i.e., through an access sheath, or may be introduced via a surgical cut down, and then advanced from the remote access site through the vasculature until they reach the heart. Thus, the procedures of the present invention will generally not require penetrations made directly through the exterior heart muscle, i.e., myocardium, although there may be some instances where penetrations will be made interior to the heart, e.g., through the interatrial septum to provide for a desired access route. While the procedures of the present invention will usually be percutaneous and intravascular, many of the tools will find use in minimally invasive and open surgical procedures as well. In particular, the tools for capturing the valve leaflets prior to attachment can find use in virtually any type of procedure for modifying cardiac valve function.

5                   The atrioventricular valves are located at the junctions of the atria and their  
respective ventricles. The atrioventricular valve between the right atrium and the right  
ventricle has three valve leaflets (cusps) and is referred to as the tricuspid or right  
10                   atrioventricular valve. The atrioventricular valve between the left atrium and the left  
5                   ventricle is a bicuspid valve having only two leaflets (cusps) and is generally referred to  
as the mitral valve. In both cases, the valve leaflets are connected to the base of the atrial  
chamber in a region referred to as the valve annulus, and the valve leaflets extend  
15                   generally downwardly from the annulus into the associated ventricle. In this way, the  
valve leaflets open during diastole when the heart atria fill with blood, allowing the blood  
10                   to pass into the ventricle. During systole, however, the valve leaflets are pushed together  
and closed to prevent back flow of blood into the atria. The lower ends of the valve  
20                   leaflets are connected through tendon-like tissue structures called the chordae, which in  
turn are connected at their lower ends to the papillary muscles. Interventions according to  
the present invention may be directed at any one of the leaflets, chordae, annulus, or  
25                   15                   papillary muscles, or combinations thereof. It will be the general purpose of such  
interventions to modify the manner in which the valve leaflets coapt or close during  
systole so that back flow or regurgitation is minimized or prevented. While the  
procedures of the present invention will be most useful with the atrioventricular valves, at  
30                   least some of the tools described hereinafter may be useful in the repair of other cardiac  
20                   valves, particularly the aortic valve.

                  The methods of the present invention will usually comprise accessing a  
35                   patient's vasculature at a location remote from the heart, advancing an interventional tool  
through the vasculature to a ventricle and/or atrium, and engaging the tool against a tissue  
structure which forms or supports the atrioventricular valve. By engaging the tool against  
25                   the tissue structure, the tissue structure is modified in a manner that reduces valve leakage  
or regurgitation during ventricular systole. The tissue structure may be any of one or  
40                   more of the group consisting of the valve leaflets, chordae, the valve annulus, and the  
papillary muscles. Optionally, the interventional tool will be oriented relative to the  
atrioventricular valve and/or tissue structure prior to engaging the tool against the tissue  
45                   30                   structure. The interventional tool may be self-orienting (e.g., pre-shaped) or may include  
active mechanisms to steer, adjust, or otherwise position the tool. Alternatively,  
orientation of the interventional tool may be accomplished in whole or in part using a  
50                   separate guide catheter, where the guide catheter may be pre-shaped and/or include active  
steering or other positioning means. In all cases, it will usually be desirable to confirm

5 the position prior to engaging the valve leaflets or other tissue structures. Such orienting step may comprise positioning the tool relative to a line of coaptation in the atrioventricular valve, e.g., engaging positioning elements in the valve commissures.

10 In a first aspect of the method of the present invention, the tissue structure  
5 comprises the valve leaflets and the engaging step comprises attaching one or more opposed points on or along the valve leaflets together. In the case of the bicuspid mitral valve, the attachment points may be located at or near the center of each leaflet, creating a  
15 generally symmetric structure with two openings, i.e., between the attachment point(s) and each of the two commissures. Alternatively, the attachment points may be close to  
10 each of the commissures. Both will effectively reduce the area in which the valve can open. In the case of the tricuspid valve, any two of the three leaflets can be partially or  
20 totally closed together or all three may be partially closed together.

In both cases, the attachment of the valve leaflets may be performed in a variety of ways, including suturing, clipping, stapling, riveting, gluing, fusing, or the like.  
25 While each of these approaches may differ significantly in the protocols and devices used for performing them, the end result will be the same, i.e., improved ability of the atrioventricular valve to close against the elevated pressures within the ventricle during  
30 systole. In order to improve apposition of the valve leaflets, it may be preferred to attach the leaflets at a point spaced inwardly from the free edge of the leaflet. Usually, the  
20 attachment point within the valve leaflet will be located from 1 mm to 4 mm inward from the free edge.

35 It will frequently be desirable to stabilize the interventional tool relative to the valve leaflets and other heart tissue structures at least some points during the interventional procedure. In a broad sense, such stabilization is intended primarily to  
25 couple motion of the interventional tool to the motion of the heart so that the tool may then engage the valve leaflets or other target tissue structures with minimum differential  
40 motion. The stabilization may be achieved either through the interventional tool or through a guide catheter or other platform which is used to deliver the interventional tool. In both cases, stabilization will usually be achieved by engaging a tissue structure of the  
45 30 heart, such as the interatrial septum, the atrial wall, the valve annulus, the valve chordae, the papillary muscles, or the like. For antegrade approaches, immobilization of either the guide catheter, the interventional tool, or both relative to the valve annulus or valve  
50 commissures will be particularly effective. For retrograde approaches, immobilization against the papillary muscles, the chordae, or the valve leaflets themselves may be



5 particularly effective. Stabilization should be distinguished from valve capture which is usually performed after the interventional tool and/or guide catheter have been stabilized within the heart. Thus, the methods of the present invention may comprise up to four  
10 separate steps or phases prior to valve affixation. First, the interventional tool and/or  
5 guide catheter may be positioned, either actively or passively. Second, the interventional tool and/or guide catheter may be stabilized within the heart. Next, the interventional tool may be used to capture the valve leaflets. Then, prior to affixation, the valve leaflets may  
15 be positioned and, if necessary, repositioned in order to determine that a particular coaptation and affixation are capable of inhibiting the valve regurgitation. Finally, once  
10 adequate regurgitation inhibition has been confirmed, the valve leaflets may be affixed in any of the manners described below.

20 In a particular approach, the interventional tool may be stabilized by mechanically fixing the shape of the tool after the tool has been advanced to a position proximate the atrioventricular valve. For example, the interventional tool can comprise a  
25 15 plurality of linked elements which can be locked into place, e.g., a "goose-neck" device. Such mechanically lockable devices may be used by themselves or in conjunction with any of the other stabilization devices described herein.

30 When attaching portions of the valve leaflets together, it will frequently be desirable to temporarily capture the valve leaflets before implementing the final  
20 attachment step. For example, the leaflets can be captured using forceps or other graspers introduced as part of or separately from the interventional tool. After capturing the valve  
35 leaflets, flow through the valve can be observed by conventional cardiac imaging techniques, such as trans-esophageal echocardiography (TEE), intracardiac echocardiography (ICE) or other ultrasonic imaging technique, fluoroscopy, angiography,  
25 catheter based magnetic resonance imaging (MRI), computed tomography (CT) and the like. By thus observing the flow through the valves, and more importantly whether or not  
40 back flow or regurgitation continues or has been sufficiently inhibited, the desired attachment configuration for the leaflets can be determined. If continued regurgitation is  
45 observed, the valve leaflets may be repositioned and the presence or absence of  
30 regurgitation again determined. Such repositioning steps may be continued until a position is identified in which the regurgitation is sufficiently inhibited. Additionally,  
50 other considerations, such as position of the attachment within the leaflet, stress placed on the leaflet, and other factors can be visualized before deciding on the final attachment point(s). In a preferred example, the valve leaflets may be coapted by a grasping

5 instrument which also has a fixation mechanism, such as stapling, suturing, clipping or  
riveting as previously described, so that once a desirable attachment configuration is  
temporarily achieved, the final attachment can be made using the same instrument.

10 Grasping of the valve leaflets can be accomplished using articulated graspers, vacuum-  
5 assisted graspers, grasping pins, or other temporary attachment modes as described in  
more detail below. After the leaflets are in the desired configuration, they may be  
permanently secured together by any of the techniques described above.

15 In a second aspect of the method of the present invention, the tissue  
structure comprises the chordae and the engaging step comprises linking opposed chordae  
10 together, i.e., chordae attached to different valve leaflets. Usually, the chordae will be  
partially gathered or coupled together using a suture or other loop structure. In some  
20 instances it may be desirable to closely tie the chordae together at one or more locations.

In a third aspect of the method of the present invention, the tissue structure  
comprises the chordae and the engaging step comprises applying energy to shorten the  
25 chordae. Particular forms of heat energy, most particularly radiofrequency energy, have  
been found to be able to modify and shrink collagen so that supporting chordae may be  
tightened. By applying energy to shorten one or more of the chordae attaching either or  
30 both (or all three in the case of the tricuspid valve) valve leaflets, the flow through the  
atrioventricular valve can be modified and regurgitation minimized. In a preferred aspect  
20 of the present invention, the chordae will be initially grasped or captured and manipulated  
to temporarily apply tension to the valve leaflets. The effect of such temporary  
35 shortening can then be visually assessed and, if a desired improvement in valve  
performance is observed, energy can be applied to shorten the chordae. In many cases,  
however, it may be preferable to apply a clip, ring, suture loop, or other mechanical  
25 element to permanently twist, plicate, or otherwise shorten the chordae, as described  
elsewhere herein.

40 In a fourth aspect of the method of the present invention, the tissue  
structure comprises the valve annulus and the engaging step comprises circumferentially  
tightening or shortening the annulus. In a preferred technique, the annulus will be  
45 strengthened by positioning and attaching a supporting structure over the annulus in a  
manner broadly analogous to the open surgical placement of an annuloplasty ring.  
Alternatively, the annulus can be tightened by surgical plication techniques, or in some  
50 instances by shrinking tissue within the annulus by applying radiofrequency energy as  
generally described above in connection with shortening of the chordae.

5 In a fifth aspect of the method of the present invention, the tissue structure  
comprises the papillary muscles and the engaging step comprises capturing and drawing  
opposed points or portions of the papillary muscles together. This approach is similar in  
10 many respects to capture of the chordae, and will generally comprise suturing or  
5 otherwise forming a linkage between the opposed portions of the papillary muscles. As  
with the chordae, it will generally not be desirable to fully close the papillary muscles  
together, although in some instances such an approach may also find use.

15 In all the aspects of the method described above, the heart will usually  
remain beating while the interventional tool is engaged against the tissue structure. When  
10 the heart is beating, however, it may be desirable to temporarily stop valve action during  
at least a portion of the procedure, particularly to facilitate grasping of the valve leaflets  
20 when such a technique is being employed. The valve action can be slowed temporarily  
by decreasing the heart rate with intravenous infusion of a beta blocker, such as esmolol,  
or can be completely stopped for a brief time, e.g., five to ten seconds, by infusion of a  
25 drug, such as adenosine. Alternatively, the valve action can be stopped by temporarily  
raising the pressure in the associated ventricle to a pressure above that in the atrium  
during diastole. While the heart will continue to beat, the motion of the valve leaflets  
opening and closing will be stopped to facilitate grasping. As a further alternative, it will  
30 be possible to mechanically restrain the leaflets directly or by capturing the chordae, as  
20 described in more detail below. While such an approach may be effective for some  
purposes, the difficulty in capturing the valve leaflets initially may still be present.

35 While the methods of the present invention are particularly desirable since  
they permit interventions to occur without stopping the heart, they may also be used with  
patients undergoing cardiopulmonary bypass. Such cardiopulmonary bypass can be  
25 achieved by any presently available technique, including both conventional systems and  
recently developed endovascular bypass systems, such as those available from Heartport,  
40 Inc., Redwood City, California.

45 During the procedures performed while the heart is beating, it will often be  
desirable to stabilize the interventional tool against one or more cardiac structures prior to  
30 grasping the leaflets with the interventional tool. Such stabilization will lessen the  
relative motion between the tool and the structure. Stabilization mechanisms may be  
separate from or integral with any part of the system or device, including but not limited  
50 to guidewires, guiding catheters and interventional tools. Likewise, the stabilization  
mechanisms may provide one or more additional functions in the tissue modification

5 procedure, such as steering, orientation assessment, grasping, coaptation, adjustment and fixation. Therefore, many components in the system may have dual purposes.

Coaptation may be performed by a number of methods, such as capturing  
10 the leaflets or by releasably capturing the chordae attached to each leaflet. An exemplary  
5 capture device will comprise a snare, or a pair of snares, which are advanced through the  
chordae to capture or entangle individual chordae. This snare or snares may then be  
tightened to draw the chordae partially together and limit valve motion, at least partially.  
15 After such coaptation is achieved, the valve leaflets, chordae, papillary muscles, or  
annulus may then be engaged and modified, e.g., the leaflets may be attached, using a  
10 separate interventional tool, as described above and elsewhere herein. Alternatively, it  
will be possible to form a permanent link, bridge, or capture of the chordae if the  
20 temporary coaptation appears sufficient to repair valve function. In some instances, it  
may be sufficient to simply detach the snare or other capture mechanism and leave it in  
place permanently. In other instances, it will be possible to exchange the snare for a more  
25 permanent attachment structure, such as a suture loop or metallic coil. For example, once  
the snare is in place, if the valve function is acceptably repaired, the snare may be drawn  
out from the chordae through the placement catheter, where the snare pulls a length of  
suture in the manner of a needle passing through tissue. The suture can then be tied or  
30 otherwise fastened to form a permanent capture loop for the chordae. Alternatively, a  
20 separate attachment structure, such as a metal coil, barb, malecot, or the like, may be  
advanced around the snared chordae to effect permanent capture, where a structure will  
be detached and left in place.

35 The methods described above may be performed using either antegrade or  
retrograde endovascular access through the vasculature. The following description will  
25 describe both antegrade and retrograde access approaches for gaining access to the mitral  
40 valve. Mitral valve access is generally more difficult than tricuspid valve access. In a  
retrograde approach, the interventional tool, optional guiding catheter, and any other  
supporting devices, will be introduced through distal arterial vasculature and over the  
aortic arch and into the left ventricle through the aortic valve. Typically, the aortic arch  
45 or via a brachial approach will be approached through a conventional femoral artery  
30 access route, but could also be approached through the brachial artery, axillary artery, or a  
carotid artery. When entering the left ventricle, the interventional tool will generally be  
50 directed downwardly and away from the mitral valve structure. Thus, the interventional  
tool will usually be curved or turned so that it approaches the mitral valve from below,

5 usually through the chordae toward the valve annulus. For example, the interventional  
tool can enter the left ventricle through the aortic valve and then be deflected or otherwise  
steered to turn 90° to directly approach the mitral valve and chordae. Steering of the tool  
10 can be accomplished by deflecting a supporting catheter using pull wires, pre-formed  
5 curved catheters, or the like. In some instances, the papillary muscles could be more  
directly accessed since they generally lie below the aortic valve and inline with the tool as  
it enters the left ventricle.

15 Often, it will be desirable to position the interventional tool toward the  
target tissue structure using a preformed and/or steerable guide catheter. In a retrograde  
10 approach, the guide catheter may be placed from an access point, e.g., the femoral artery  
at the patient's groin, so that it passes over the aortic arch, through the aortic valve, and  
20 into the left ventricle where it will form an access path to the target tissue structure.  
When the tissue structure is the chordae or valve leaflets, the guide catheter will usually  
have to be curved or be everted or turned backward so that it can turn the interventional  
25 tool around. Additionally, it may be desirable to provide for stabilization of the distal end  
of the guide catheter. Stabilization may be provided by extendible elements, wires, cages,  
balloons, or other structures which engage the valve annulus, chordae or ventricular wall  
portions. Alternatively, two or more stabilizing extensions may be provided to project  
30 forwardly from the guide catheter and seat in the valve commissures to position and hold  
20 the guide catheter in place. Such extendible elements may also be used to stabilize  
guidewires, interventional tools and other types of catheter systems. Specific stabilization  
structures will be described in more detail below.

35 Access for an antegrade endovascular approach will be through the inferior  
vena cava or superior vena cava into the right atrium. Such antegrade access may, in  
25 itself, be sufficient to perform procedures on the tricuspid valve from the top of the valve.  
Such procedures, however, will not be described in detail herein. To access the mitral  
40 valve, it will be necessary to pass from the right atrium into the left atrium, typically by  
passing the tool through the interatrial septum. The interatrial septum may be  
endovascularly penetrated by conventional techniques, typically using a Brockenbrough  
45 needle, as described in the valvuloplasty literature. Once the interatrial septum has been  
30 penetrated, the interventional tool may be passed into the left atrium so that it approaches  
the mitral valve from the top. Such an approach will require that the access path turn  
50 downward, typically through an angle in the range from 0° to 120°.

5 The superior vena cava may be accessed through a variety of conventional peripheral access sites, such as the internal jugular vein, while the inferior vena cava may be accessed through the femoral vein. Such access may be performed percutaneously or by surgical cut down techniques.

10 As with the retrograde arterial approach, the antegrade venous approach may utilize placement of a guide catheter. With the use of a guidewire, the guide catheter will be configured to pass from the initial access location, through either the superior vena cava or inferior vena cava into the right atrium. The guide catheter will then be adapted to pass through an interatrial penetration and into the left atrium, where it will be pre-shaped or deflected to approach the mitral valve from the top. The guidewire, guide catheter and/or the interventional catheter which carries the interventional tool may be steerable and may optionally have stabilizing elements. For example, in this specific embodiment, the guide catheter may have two or more laterally extensible steering wires and/or a plurality of stabilizing arms which project forwardly and seat around the valve annulus or commissures to hold the guide catheter in place. The interventional tool may then be deployed through the guide catheter to perform the desired valve repair technique.

25 Systems according to the present invention comprise a guide catheter configured to pass from the remote vasculature of a patient to a position within the heart adjacent to a target atrioventricular or other cardiac valve. The systems further comprise an interventional catheter configured to pass through the guide catheter and to engage the atrioventricular or other cardiac valve and/or associated cardiac structures and an interventional tool on the interventional catheter adapted to modify the atrioventricular or other cardiac valve leaflets, valve annulus, valve chordae or papillary muscles to reduce regurgitation. In particular, the guide catheter can be configured for either an antegrade or retrograde approach to the mitral valve, as described above. The guide catheter may further comprise a stabilizing element for engaging tissue within the heart to reduce relative movement between the guide catheter and the tissue while the heart remains beating. The structure can be any of the cages, wires, or the like, which have previously been described in connection with the method. Additionally, the interventional catheter may also comprise a stabilizing element for engaging a tissue structure within the heart to reduce relative motion between the interventional catheter and the tissue. The stabilizing element can also be an expansible cage, steering wires, or the like and may include vacuum and/or surface finishes to enhancing coupling. Specific interventional tools

5 include suturing devices, stapling devices, clip-applying devices, radiofrequency electrodes, surgical adhesive applicators, annuloplasty rings, and the like.

Both the interventional tool and the guide catheter may employ stabilizing mechanisms intended to engage a tissue structure within the heart to reduce relative movement between the interventional tool and/or guide catheter relative to the heart, and in particular relative to the atrioventricular valve. The stabilization mechanisms in both cases may be the same. Typically, the stabilization mechanisms will be adapted to engage at least one tissue structure selected from the group consisting of the interatrial septum, the atrial wall, the valve annulus, the valve commissures, the valve chordae, and the papillary muscles. For example, the stabilizing mechanism may comprise one or more extensible wires which are deployable radially outwardly to engage the tissue structure, such as the valve commissures. Alternatively, the stabilizing mechanism could comprise an expansible cage that can be deployed to occupy all or at least a major portion of the atrium above the atrioventricular valve. As a still further alternative, the stabilizing mechanism could be a pair of inflatable balloons which are spaced-apart and adapted to engage the interatrial septum when the interventional tool and/or guide catheter are passed therethrough.

In further specific aspects of the systems of the present invention, the interventional tool may comprise a valve leaflet capture device intended for temporarily holding the valve leaflets prior to modification, e.g., affixation. For example, the valve leaflet capture device may comprise a pair of extensible elements which may be advanced from a distal end of the interventional tool to engage and capture the two mitral valve leaflets or three aortic valve leaflets. The particular capture tools may grasp the leaflets by pinching, partially or fully penetrating or piercing, and/or suctioning the leaflets. The tools may comprise jawed devices, looped devices, coiled devices or pronged devices, or vacuum devices to grasp and hold the leaflets.

The present invention further provides methods for grasping an atrioventricular or other cardiac valve, particularly the mitral valve, to facilitate subsequent intervention or for other purposes. The grasping method comprises capturing chordae attached to at least one leaflet of the valve while the heart is beating. Capture of the chordae from beneath the valve can modify leaflet movement and improve valve function, optionally closing portions of opposed valve leaflets against each other. Usually, chordae attached to valve leaflets (or possibly three valve leaflets in the case of tricuspid valves) are captured simultaneously. For example, one or more snares, such as

5 helical coils, can be advanced into the chordae to capture and immobilize portions thereof. Alternatively, a loop element can be advanced through the valve chordae and tightened in order to modify valve function. In some instances, capture of the chordae  
10 can be made permanent and will be sufficient to treat the underlying regurgitation. In other cases, capture of the chordae will be primarily for leaflet coaptation, and the leaflets will be affixed by a subsequent interventional step. Preferably, the subsequent  
15 interventional step is performed while the chordae remain captured. The chordae can then be released after the leaflets or other tissue structures have been modified.

The present invention still further provides a chordae capture catheter  
10 comprising a catheter body having a proximal end and a distal end. Means are provided at or near the distal end of the catheter body for capturing the chordae. A first exemplary  
20 means comprises one or more coils which are extensible from the distal end of the catheter and which engage and entangle the chordae when they are advanced therein. A second exemplary capture means comprises a loop element which is extensible from the  
25 distal end of the catheter and which is pre-formed to pass through the chordae on one or both, preferably both valve leaflets in order to draw the chordae together and modify valve function.

A further method according to the present invention for grasping an  
30 atrioventricular or other cardiac valve leaflets comprises capturing two valve leaflets separately and preferably sequentially. Such capture is effected by a leaflet capture  
20 catheter having at least three grasping jaws or prongs. A first valve leaflet is captured between a first pair of prongs, and second valve leaflet is captured between a second pair  
35 of prongs. Optionally, the two prong pairs can have a common center prong, typically where the center prong is fixed (immobile) and the two outer prongs pivot in order to  
25 provide a pair of adjacent jaw-type graspers. By separately and sequentially grasping the two leaflets, the leaflets can be held in a preferred apposition and the improvement in  
40 valve function observed. Alternatively, the leaflets may be grasped simultaneously. If the improvement is adequate, the valves can be permanently affixed in a separate step. Optionally, the leaflet capture catheter can include a device for fixing the valves, e.g., it  
45 can carry a clip which can be applied on to the valves as the capture catheter is withdrawn.

The present invention still further provides leaflet capture catheters suited  
50 for performing the method just described. The catheters comprise a catheter body having a proximal end and a distal end. A leaflet grasper is provided at or near the distal end of



5 the catheter body and includes at least three prongs wherein at least two of the three  
prongs are pivotable so that they may be separately actuated to separately capture  
individual leaflets or simultaneously actuated to capture the leaflets together. Optionally,  
10 the catheters further comprise means for affixing the valve leaflets after they have been  
5 captured, preferably comprising a clip-applier.

The present invention further includes leaflet capture catheters and tools  
which utilize a vacuum for grasping the valve leaflets and manipulating the post leaflets  
15 into a desired apposition. Usually, the catheter will have at least two vacuum channels at  
a distal end where the channels are preferably separately positionable and independently  
10 actuable. In that way, at least two valve leaflets can be separately captured and  
positioned while the base catheter remains stationary. The catheter may be positioned in  
20 an antegrade or retrograde manner with the tool entering between the valve leaflets and  
optionally between the chordae. The tool and/or catheter may optionally further include  
modification devices, such as suture appliers, clip appliers, staplers, rivet appliers,  
25 adhesive applicators, heating elements for shortening the chordae, and others of the  
specific interventional tools described hereinafter. Likewise, the present invention further  
includes catheters and tools which include lumens for monitoring pressures within the  
chambers of the heart, and/or infusion of radiopaque contrast solution.

#### BRIEF DESCRIPTION OF THE DRAWINGS

20 Fig. 1 is a schematic illustration of the left ventricle of a heart showing  
blood flow during systole with arrows.

35 Fig. 2 is a schematic illustration of the left ventricle of a heart having  
prolapsed leaflets in the mitral valve.

40 Fig. 3 is a schematic illustration of a heart in a patient suffering from  
25 cardiomyopathy where the heart is dilated and the leaflets do not meet.

Fig. 3A shows normal closure of the leaflets, while Fig. 3B shows  
abnormal closure in the dilated heart.

45 Fig. 4 illustrates mitral valve regurgitation in the left ventricle of a heart  
having impaired papillary muscles.

30 Fig. 5 is a schematic illustration showing direct attachment of opposed  
valve leaflets to reduce valve regurgitation according to the methods of the present  
invention.

50

55

5 Fig. 6 is a schematic illustration showing attachment of valve chordae to treat valve regurgitation according to the methods of the present invention.

10 Figs. 7-8 show exemplary antegrade approaches to the mitral valve from the venous vasculature.

5 Figs. 9-10 show exemplary retrograde approaches to the mitral valve through the aortic valve and arterial vasculature.

Figs. 11-14 illustrate the use of adjustment wires for steering capability.

15 Figs. 15A-15D illustrate the use of pre-shaped mandrels to steer a component or structure.

10 Figs. 16-20, 21A-21C, and 22A-22B depict various orientation assessment tools.

20 Fig. 23 is a schematic illustration of an interatrial septum stabilization device.

25 Fig. 24 is a schematic illustration of a catheter shaft designed to provide stabilization against a structure, such as the interatrial septum, or for flexible adjustment and locking stability in various positions.

Fig. 25 is a schematic illustration of an atrial stabilization device.

30 Figs. 26-29 illustrate stabilization mechanisms which utilize coupling to the valve annulus.

20 Figs. 30, and 31A-31D illustrate stabilization mechanisms which utilize coupling with the valve commissures and/or leaflets.

35 Figs. 32A and 32B illustrate mitral valve stabilization using snares for capturing the valve chordae.

25 Figs. 33A and 33B illustrate an antegrade approach for snaring valve chordae and optionally suturing the chordae together to treat valve regurgitation.

40 Fig. 34 illustrates an antegrade approach for snaring valve chordae to stabilize the mitral valve.

Figs. 35 and 35A illustrate a snaring catheter particularly intended for capturing valve chordae from a retrograde approach.

45 30 Figs. 36A and 36B illustrate use of the catheter Fig. 35 for snaring valve chordae.

50 Figs. 37 and 38 illustrate a catheter similar to that shown in Figs. 35 and 35A, except that it includes a working channel for introducing interventional catheters

5 and tools to treat the mitral or other atrioventricular valve according to the methods of the present invention.

10 Figs. 39A and 39B illustrate a coil which can be implanted within the valve chordae to stabilize the mitral valve.

5 Fig. 40 illustrates placement of the coil of Figs. 39A and 39B from a retrograde approach.

15 Figs. 41A-41B, 42A-42B and 43 illustrate valve leaflet grasping devices which utilize a pinching method.

10 Figs. 44A-44D are schematic illustrations of an atrial-ventricular valve leaflet grasping device which utilizes a pinching method.

20 Figs. 45A-45B are schematic illustrations of a grasping device which utilizes rollers in a pinching method.

Figs. 46A-46B are schematic illustrations of a grasping device which utilizes a pair of opposing coils in a pinching method.

25 Figs. 47A-D illustrate a pronged valve leaflet device which utilizes a pinching, partially penetrating or piercing method.

Fig. 48 illustrates a vacuum-assisted stabilization catheter for use in the methods of the present invention.

30 Fig. 49 illustrates an embodiment of a valve suturing device according to the present invention.

35 Figs. 49A-49C illustrate an additional embodiment of a valve suturing device according to the present invention.

Fig. 50 illustrates a further embodiment of a valve suturing device according to the present invention.

25 Fig. 51 illustrates use of the catheter for capturing and suturing opposed mitral valve leaflets.

40 Fig. 52 illustrates the mitral valve leaflets which have been secured as shown in Fig. 51.

45 Figs. 53 and 54 illustrate an alternative anchor which can be used with the suturing devices of the present invention.

Figs. 55A-55B illustrate the use of an expansible anchor in fixation.

50 Figs. 56 and 57 illustrate yet another suturing device according to the present invention.

5

Fig. 58 illustrates use of the suturing device of Figs. 56 and 57 to place sutures between valve leaflets of the mitral valve.

10

Fig. 59 illustrates yet another embodiment of a suturing device according to the present invention.

5

Fig. 60 illustrates use of the device of Fig. 59 and suturing opposed mitral valve leaflets.

15

Figs. 61A and 61B illustrate a stapling device which can be used to staple opposed leaflets of an atrioventricular valve according to the methods of the present invention.

10

Figs. 62A-D are schematic illustrations of fixation devices.

20

Fig. 63 illustrates an alternative two part fixation stapling device.

Fig. 64 illustrates use of the stapling device of Fig. 63 for stapling opposed valve leaflets of a mitral valve.

25

15

Fig. 65A-65C are schematic illustrations of coiled fixation devices.

Fig. 66 illustrates use of a self-securing anchor for attaching opposed surfaces on the leaflets of the mitral valve.

30

Figs. 66A-66B are schematic illustrations of penetrating fixation devices.

Figs. 67 and 68 are schematic illustrations of penetrating fixation devices with barb-like distal ends.

20

Figs. 69A-C and 70A-B are schematic illustrations of clips used as fixation devices.

35

Figs. 71, and 72A-72B are schematic illustrations of clips involving the use of graspers in the fixation mechanism.

Figs. 73A-73C illustrate a three-jaw clip-applier.

25

Fig. 74 illustrates a clip which has been applied by the clip-applier of Figs. 73A-73C.

40

Fig. 75 illustrates a device for applying radiofrequency energy to shorten valve chordae.

45

30

Figs. 76, and 77A-77B illustrates devices used to plicate and shorten valve chordae.

Fig. 78 illustrates a first exemplary approach for placing an annuloplasty ring according to the methods of the present invention.

50

Figs. 79 and 80 illustrate a second exemplary approach for placing an annuloplasty ring according to the methods of the present invention.

55

Fig. 81 illustrates a method for placing an anchored filament about a mitral valve annulus that can be used to tighten the annulus.

Fig. 82 illustrates a method for placing multiple sutures about a mitral valve annulus, where the individual suture plicate and tighten the annulus.

Figs. 83-85 illustrate an embodiment of an atrial device for valve tissue modification.

Figs. 86, and 87A-87C illustrate an embodiment of an atrial-ventricular device for valve tissue modification.

Figs. 88-89, and Figs. 90A-90B illustrate an embodiment of a ventricular device for valve tissue modification.

## DESCRIPTION OF THE SPECIFIC EMBODIMENTS

### I. CARDIAC PHYSIOLOGY

The left ventricle LV of a normal heart H in systole is illustrated in Fig. 1. The left ventricle LV is contracting and blood flows outwardly through the tricuspid (aortic) valve AV in the direction of the arrows. Back flow of blood or "regurgitation" through the mitral valve MV is prevented since the mitral valve is configured as a "check valve" which prevents back flow when pressure in the left ventricle is higher than that in the left atrium LA. The mitral valve MV comprises a pair of leaflets having free edges FE which meet evenly to close, as illustrated in Fig. 1. The opposite ends of the leaflets LF are attached to the surrounding heart structure along an annular region referred to as the annulus AN. The free edges FE of the leaflets LF are secured to the lower portions of the left ventricle LV through chordae tendineae CT (referred to hereinafter as the chordae) which include plurality of branching tendons secured over the lower surfaces of each of the valve leaflets LF. The chordae CT in turn, are attached to the papillary muscles PM which extend upwardly from the lower portions of the left ventricle and interventricular septum IVS.

Referring now to Figs. 2-4, a number of structural defects in the heart can cause mitral valve regurgitation. Ruptured chordae RCT, as shown in Fig. 2, can cause a valve leaflet LF2 to prolapse since inadequate tension is transmitted to the leaflet via the chordae. While the other leaflet LF1 maintains a normal profile, the two valve leaflets do not properly meet and leakage from the left ventricle LV into the left atrium LA will occur, as shown by the arrow.

5                   Regurgitation also occurs in the patients suffering from cardiomyopathy  
where the heart is dilated and the increased size prevents the valve leaflets LF from  
meeting properly, as shown in Fig. 3. The enlargement of the heart causes the mitral  
annulus to become enlarged, making it impossible for the free edges FE to meet during  
10                   systole. The free edges of the anterior and posterior leaflets normally meet along a line of  
coaptation C as shown in Fig. 3A, but a significant gap G can be left in patients suffering  
from cardiomyopathy, as shown in Fig. 3B.

15                   Mitral valve regurgitation can also occur in patients who have suffered  
ischemic heart disease where the functioning of the papillary muscles PM is impaired, as  
10                   illustrated in Fig. 4. As the left ventricle LV contracts during systole, the papillary  
muscles PM do not contract sufficiently to effect proper closure. The leaflets LF1 and  
20                   LF2 then prolapse, as illustrated. Leakage again occurs from the left ventricle LV to the  
left atrium LA, as shown by the arrow.

## 25                   II. INTERVENTIONAL APPROACHES

15                   The present invention treats cardiac valve regurgitation, particularly mitral  
valve regurgitation, by intervention at either of two locations. First, as shown in Fig. 5,  
the valve leaflets LF may be directly attached or coupled to each other by a structure S or  
30                   other means. Typical structures include suture, staples, clips, pins, or other closure  
devices of a type commonly used in attaching opposed tissue surfaces. Alternatively, the  
20                   opposed surfaces on the valve leaflets could be attached using adhesives, fusion energy,  
including radiofrequency current, laser energy, microwave, ultrasonic energy, or the like.  
35                   A variety of specific techniques for valve leaflet attachment will be described hereinafter.

                  A second and often preferred interventional point will be in the chordae, as  
shown in Fig. 6. There, an attachment structure S is shown to couple individual chordae,  
25                   or tendons which are attached to each of the two leaflets LF. A variety of specific  
40                   structures can be utilized, such as snares, staples, sutures, coils, clips, snaps, rivets,  
adhesives, and the like. Opposed chordae will usually also be attached directly,  
optionally employing any of the same structures listed above. Alternatively, opposed  
45                   chordae may be indirectly tied or coupled together by a structure which links or couples  
30                   their movement, but which does not physically attach chordae from each of the valve  
leaflets directly together. In addition to attaching the chordae, chordal intervention can  
include shortening the chordae, e.g., by applying energy to shrink the collagen therein, or  
50                   may utilize mechanical plication devices, such as clips, to physically shorten the chordae.

### III. ACCESS TO THE MITRAL VALVE

Access to the mitral valve or other atrioventricular valve will preferably be accomplished through the patient's vasculature in a "percutaneous" manner. By "percutaneous" it is meant that a location of the vasculature remote from the heart is accessed through the skin, typically using a surgical cut down procedure or a minimally invasive procedure, such as using needle access through, for example, the Seldinger technique. The ability to percutaneously access the remote vasculature is well-known and described in the patent and medical literature. Depending on the point of vascular access, the approach to the mitral valve may be "antegrade" and require entry into the left atrium by crossing the interatrial septum. Alternatively, approach to the mitral valve can be "retrograde" where the left ventricle is entered through the aortic valve. Once percutaneous access is achieved, the interventional tools and supporting catheter(s) will be advanced to the heart intravascularly where they may be positioned adjacent the target cardiac valve in a variety of manners, as described elsewhere herein. While the methods will preferably be percutaneous and intravascular, many of the tools described herein will, of course, also be useful for performing open surgical techniques where the heart is stopped and the heart valve accessed through the myocardial tissue. Many of the tools will also find use in minimally invasive procedures where access is achieved thoroscopically and where the heart will usually be stopped but in some instances could remain beating.

A typical antegrade approach to the mitral valve is depicted in Figs. 7 and 8. The mitral valve MV may be accessed by an approach from the inferior vena cava IVC or superior vena cava SVC, through the right atrium RA, across the interatrial septum IAS and into the left atrium LA above the mitral valve MV. As shown in Fig. 7, a catheter 10 having a needle 12 may be advanced from the inferior vena cava IVC into the right atrium RA. Once the catheter 10 reaches the anterior side of the interatrial septum IAS, the needle 12 may be advanced so that it penetrates through the septum at the fossa ovalis FO or the foramen ovale into the left atrium LA. At this point, a guidewire may be exchanged for the needle 12 and the catheter 10 withdrawn.

As shown in Fig. 8, access through the interatrial septum IAS will usually be maintained by the placement of a guide catheter 14, typically over a guidewire 16 which has been placed as described above. The guide catheter 14 affords subsequent access to permit introduction of the interventional tool(s) which will be used for performing the valve or tissue modification, as described in more detail below.

5 The antegrade approach to the mitral valve, as just described, is  
advantageous in a number of respects. For example, the use of the antegrade approach  
will usually allow for more precise and effective centering and stabilization of the guide  
10 catheter and/or interventional tool. Precise positioning, of course, facilitates accuracy in  
5 the tissue modification, particularly affixation of the valve leaflets or chordae. The  
antegrade approach also reduces the risk of damaging the subvalvular apparatus during  
catheter and interventional tool introduction and manipulation. Additionally, the  
15 antegrade approach eliminates the risks associated with crossing the aortic valve. This is  
particularly relevant to patients with prosthetic aortic valves which cannot be crossed.  
20 When employing chordal fixation, the tools can be placed very close to the free edge of  
the leaflet since they will be removed in a direction away from the chordae which are  
being fixed. Additionally, an antegrade approach allows more direct access to the valve  
25 leaflets unimpeded by presence of the chordae.

A typical retrograde approach to the mitral valve is depicted in Fig. 9.  
15 Here the mitral valve MV may be accessed by an approach from the aortic arch AA,  
across the aortic valve AV, and into the left ventricle below the mitral valve MV. The  
aortic arch AA may be accessed through a conventional femoral artery access route, as  
well as through more direct approaches via the brachial artery, axillary artery, or a radial  
30 or carotid artery. Such access may be achieved with the use of a guidewire 42. Once in  
20 place, a guide catheter 40 may be tracked over the guidewire 42. The guide catheter 40  
affords subsequent access to permit introduction of the interventional tool(s) which will  
be used for performing the valve or tissue modification, as described in more detail  
35 below.

In some instances, a retrograde arterial approach to the mitral valve will be  
25 preferred due to its advantages. Use of the retrograde approach will eliminate the need  
for a trans-septal puncture. The retrograde approach is also more commonly used by  
40 cardiologists and thus has the advantage of familiarity. Additionally, the retrograde  
approach provides more direct access to the chordae.

The interventional tool(s) used for performing the valve or tissue  
45 30 modifications may be specifically designed for the approach or they may be  
interchangeable. For example, tools may be specifically designed for an antegrade or  
retrograde approach, or they may be designed to be used with either approach. In any  
50 case, tools may be used in any appropriate fashion to achieve a desired result. However,  
for the sake of clarity, a nomenclature has been developed to describe the common usage



5 of such tools. Tools which perform the modification procedure while primarily residing  
primarily in the atrium are referred to as "atrial" tools. These utilize an antegrade  
approach. Tools which perform the modification procedure while primarily residing in  
10 the ventricle are referred to as "ventricular" tools, and likewise utilize a retrograde  
5 approach. Tools which cross over the valve to perform the modification procedure,  
residing in both the atrium and the ventricle, are referred to as "atrial-ventricular" tools,  
and may utilize either an antegrade or retrograde approach.

#### 15 IV. ORIENTATION STEERING

Approaching the desired valve or tissue structure for effective treatment,  
10 as described above, requires proper orientation of the catheters, tools and devices used  
throughout the procedure. Such orientation may be accomplished by gross steering of the  
20 device to the desired location and then refined steering of the device components to  
achieve a desired result.

Gross steering may be accomplished by a number of methods. First, a  
25 steerable guidewire may be used to introduce a guide catheter, interventional tool and/or  
15 treatment device into the proper position. The guide catheter may be introduced, for  
example, using a surgical cut down or Seldinger access to the femoral artery in the  
30 patient's groin. After placing a guidewire, the guide catheter may be introduced over the  
guidewire to the desired position. Alternatively, a shorter and differently shaped guide  
20 catheter could be introduced through the other routes described above.

Second, a guide catheter may be pre-shaped to provide a desired  
35 orientation relative to the mitral valve. For example, as shown in Figs. 9 and 10, guide  
catheter 40 may have a pre-shaped J-tip which is configured so that it turns toward the  
mitral valve MV after it is placed over the aortic arch AA and through the aortic valve  
40 AV. As shown in Fig. 9, the guide catheter 40 may be configured to extend down into the  
left ventricle LV and to evert so that the orientation of an interventional tool or catheter is  
more closely aligned with the axis of the mitral valve MV. The guide catheter 40 of Fig.  
45 10 orients an interventional catheter (not shown) in a lateral direction relative to the  
access of the mitral valve MV. Each of the guide catheters 40 shown in Figs. 9 and 10  
30 may find use under different circumstances. For example, the guide catheter 40 of Fig. 10  
might be particularly suited for introducing tools which modify the chordae CT, while the  
catheter 40 of Fig. 9 may be more useful for engaging tools against the valve leaflets. As  
50 shown in Fig. 9, a guidewire 42 may be positioned from the tip of the guide catheter 40

5 directly through the opening of the mitral valve MV. Interventional tools can then be directed over the guidewire 42 to form the particular procedures described hereinafter. Likewise, the interventional tool itself may be pre-shaped to provide a desired orientation.

10 Third, the guidewire, guide catheter or interventional tool may be actively deflected, e.g., having push/pull wires which permit selective deflection of the distal end in 1, 2, 3, or 4 directions depending on the number of pull wires, having shape memory nitinol, or having balloons, wires, wire cages or similar mesh structures to direct the device away from a cardiac structure and therefore into a desired position, to name a few.

15 Either of the guide catheters 40 shown in Figs. 9 or 10 may be provided with steering capabilities. For example, two or more adjustment wires 46 may be provided at the distal tip of the guide catheter 40 as shown in Fig. 11. These adjustment wires may be active or passive, and may be positioned within the valve commissures to enhance alignment of the guide catheter with the mitral valve MV. As shown in Figs. 12A and 12B, the adjustment wires 46 may be positioned in the medial commissure MVC and lateral commissure LVC, and the guide catheter 40 may thus be moved from a central location, as shown in Fig. 12A to a more medial position, as shown in Fig. 12B. The catheter could of course also be moved in the lateral direction (not shown). The ability to position the guide catheter will be of great benefit in performing the specific interventions and valve modifications described hereinafter. It will be appreciated that similar steering mechanisms could be provided on an interventional catheter introduced through the guide catheter, and in some instances it may be most desirable to provide the guidewire, the guide catheter, and the interventional catheter with steering and positioning capabilities.

35 Steering wires 50 on a guide catheter 40 may also be provided to engage opposed surfaces within the left ventricle LV, as shown in Fig. 13. By providing such a steering capability, the distal tip of the guide catheter 40 can be moved further downward from the mitral valve. Catheter 40 of Fig. 13 would be particularly useful in combination with an interventional catheter which itself has steering capabilities which engage portions of the mitral valve, such as the valve commissures as described above.

45 As shown in Fig. 14, the guidewire 52 may have laterally deflectable steering elements 54 which may be positioned in, for example, the valve commissures as described previously. This way, the guidewire 52 may be positioned toward the medial or lateral sides of the mitral valve MV, and an interventional catheter 56 introduced over the guidewire to a desired target structure within or surrounding the mitral valve MV. Providing such a steerable and positionable guidewire, it is particularly advantageous

5 when it is desired to position the tip of an interventional catheter 56 at a region well below the opening of the mitral valve. That is, neither the guide catheter nor the interventional catheter have to be advanced fully to the opening of the mitral valve, leaving them free to be positioned elsewhere.

10 5 In some instances, it will be desirable to introduce interventional tools sequentially or simultaneously from both the antegrade and retrograde directions. While it will be possible to separately introduce guiding catheters and guidewires by the approaches described above, in at least some instances it may be preferable to pass a single guidewire between the vena cava and the right atrium, crossing the interatrial 15 septum as previously described. The guidewire may then pass in an antegrade direction through the aortic valve, through the ascending and descending aorta, and then percutaneously out of the vasculature at a location remote from the heart, such as the femoral artery. 20

Location of a single guidewire in this manner provides a continuous "rail" 25 through the heart, allowing placement of separate devices in both an antegrade and retrograde direction. Additionally, any interaction or cooperation between the devices is facilitated since they will necessarily advance toward one another in an alignment which is controlled and assured by the guidewire, e.g., when fully advanced any two devices will necessarily meet. Thus, one device would extend inward from the venous side of the 30 heart in an anterior antegrade direction to the mitral valve, and a second device would enter through the arterial side of the heart in a retrograde direction. The two devices would then be precisely located relative to each other as they approach and optionally meet at or near the mitral valve. In a particular example, a stabilizing catheter could be introduced in a retrograde direction to approach the chordae and underside of the mitral 35 valve leaflets to provide for temporary stabilization and/or leaflet coaptation, as generally described above. A catheter carrying a fixation device could then be advanced in an antegrade direction to approach the valve leaflets from above. The second device could then be separately actuated to affix the valve leaflets once the proper temporary stabilization has been achieved with the first device. 40

45 30 Fourth, the guidewire, guide catheter or interventional tool may be positioned with the use of a floating balloon. This may be most useful for use with an antegrade approach. The distal balloon of a balloon tipped guidewire or balloon tipped floppy catheter may be inflated and floated antegrade through the mitral valve. If the 50 heart is slowly beating, blood will be flowing from the left atrium, through the mitral

5 valve to the left ventricle. A floating balloon may be carried along this flow trajectory, carrying the guidewire or catheter with it. The balloon may then be deflated and newly placed guidewire or catheter may be utilized as desired.

10 Fifth, a hollow guidewire, guide catheter or interventional or other tool  
5 may be positioned with the use of a rigid, pre-shaped mandrel or insertable member. As shown in Figs. 15A-D, the mandrel 600 may be comprised of wire, metal, plastic or any suitable material that may be formed to hold a desired shape 601, such as a bend or bump.  
15 The mandrel 600 may then be inserted into a lumen in a flexible structure 602 to be positioned. Such a structure may be a hollow guidewire, guide catheter, interventional  
10 tool or any other tool or component of a structure. As the shape 601 is advanced, the flexible structure 602 conforms to the shape 601 as it is passed through. This may be  
20 utilized to position a structure or component of a structure in a desired location for later steps in the procedure.

It may be appreciated that any of the devices, systems and methods used  
25 for gross steering may be also be applied to refined steering of the device or device components to achieve a desired result. In particular, it may be desired to independently or dependently manipulate components of the interventional tools throughout the  
30 procedure. Such steering may allow urging of the components relative to the leaflets, annulus, atrial wall or other specific cardiac structures. This may be achieved with any of  
20 the devices or methods described above.

#### 35 V. ORIENTATION ASSESSMENT

Proper orientation of the systems and devices is necessary for performing  
the valve or tissue modification. Both the orientation of the devices and the components of the devices, in relation to cardiac structures and to each other, are of concern. Cardiac  
40 25 structures to which orientation is desired may include the atrial walls, interatrial septum, valve annulus, valve leaflets, valve commissures, valve chordae, papillary muscles and ventricle walls, to name a few. Assessment of the orientation of the components and devices may be achieved by a number of mechanisms and methodologies.

45 First, orientation may be assessed by tactile feedback. Introduction and  
30 manipulation of the devices and components may allow them to contact cardiac structures or other devices. Such contact may guide the devices into proper position and relevant orientation. For example, it may be possible to tactilely sense the force of the distal end  
50 of a guidewire, catheter or interventional tool against the leaflets, commissures, annulus,

5 chordae, papillary muscles, ventricular walls, and/or atrial walls, to name a few. The force may be translated along its length to its proximal end to provide feedback to the physician or operator. Similarly, sensors may be used to achieve a similar result.

10 Additionally, the catheter or tool may have a lumen to allow for pressure monitoring.

- 5 This may provide feedback throughout the procedure which may indicate the presence and level of mitral regurgitation.

15 Second, orientation may be assessed by visualization of the devices and components themselves. The components or the overall system may be modified for enhanced echogenic and/or fluoroscopic visibility. Echogenicity of a material in a blood  
10 medium is dependent on the difference in acoustic impedance (product of velocity of sound and density of the medium through which the sound wave is traveling) between the  
20 material and blood. Therefore, a thin polymer coating on the components or the overall system may provide modulation of the acoustic impedance at the interface of the component and blood, thereby improving echovisibility. Likewise, microscopic air  
15 bubbles trapped on the surface or embedded within the coating may also improve echovisibility. Similarly, fluoroscopic visibility may be improved with radiopaque coatings, radiopaque marker bands, or the like. Additionally, a lumen within the catheter or tool may be provided to inject radiopaque contrast solution to improve fluoroscopic  
30 visibility or surrounding tissues. In any case, such coatings, markings and fluids may provide visualization of the devices and components themselves or any structures or elements used throughout the treatment procedure. Similarly, angioscopic vision may be used to access the orientation throughout the procedure.

35 Third, one or more orientation elements may be used to assess orientation of the components and/or systems in relation to cardiac structures, specifically the target  
25 valve. Thus, orientation elements may be any structure or feature that provides information as to the orientation of the component, device or system of the present invention. The elements may be separate from or integral with any part of the system or device. They may be removably or fixedly mounted on the guidewire, guide catheter, interventional tool and/or other device. Likewise, the elements may be components or  
45 parts of components of the device which provide one or more additional functions in the tissue modification procedure, such as stabilization, grasping, coaptation, adjustment or fixation. Further the elements may be atrial, ventricular or atrial-ventricular devices such that they may or may not cross the valve in the orientation assessment process. In  
50

5 addition, such elements may be used to steer and/or orient the components and systems prior to or simultaneous with assessment.

10 Orientation elements may be in the form of propellers, wings, petals, arms, loops, and the like. One or more of these elements may be present, typically extending radially from a central shaft. When two elements are present, they are commonly placed 120 to 180 degrees apart around the central shaft; more than two elements are typically arranged in a radial pattern around the central shaft. In the preferred embodiments, the orientation elements are typically placed either perpendicular to the line of coaptation or following the line of coaptation. This may provide the most useful reference, however 15 many other placement orientations may be used.

20 Examples of orientation elements placed perpendicular to the line of coaptation are depicted in Figs. 16 and 17. Fig. 16 is a short axis view of the mitral valve MV with an orientation element 612 shown having a pair of orientation structures 613 arranged 180 degrees apart around a central shaft 614. The orientation element 612 is shown perpendicular to the line of coaptation C. Such positioning of the element 612 25 may indicate that the device is in its desired orientation, specific components are in a desired orientation, or devices or components may be oriented in relation to the positioned element which may be more visible than other parts of the device.

30 Fig. 17 is a long axis view of the mitral valve MV. Here, a guidewire 615 with a pair of orientation propellers 616 is shown inserted through the mitral valve MV via a retrograde approach. Visualization of the propellers 616 may allow repositioning of the guidewire 615 until the propellers are perpendicular to the line of coaptation C. At 35 this point, a guide catheter, interventional or other tool may be tracked over the catheter in the desired orientation. Such tracking may be facilitated with the use of a keyed, notched, oval or similar lumen for guidance. Similarly, such orientation propellers 616 25 may be mounted on a guide catheter with a keyed lumen for guided insertion of interventional tools.

45 Examples of orientation elements placed along the line of coaptation are depicted in Figs. 18 and 19. Fig. 18 is a long axis view of an orientation element 620 inserted into the valve opening along the line of coaptation C. An end view shown in Fig. 19 illustrates the penetration of the element 620 through the valve opening and the valve leaflets LF sealing against the element 620. In addition, portions of the orientation 30 element 620 may contact the commissures CM at each end of the valve opening for support and/or for reference. Using the position of the orientation element 620 as a 50

5 reference, the location of a variety of cardiac structures, particularly the valve leaflets LF, are known. In addition, if the position of specific components of the device are known in relation to the orientation elements 620, such relation may be used to infer the relation of those components to the cardiac structures. For example, if the orientation elements are  
10 known to be perpendicular to the graspers of the present invention, positioning of the orientation elements in the manner described above would ensure that the graspers would be aligned perpendicular to the line of coaptation C or in a desirable location to grasp the valve leaflets LF.  
15

In this example, the orientation element 620 is shown as an inflatable  
10 bladder coaxially attached to a distal central shaft 621. Such a bladder may be comprised of a compliant or noncompliant material, such as PET, PUR, Silicone, Chronoprene, or the like. The bladder material itself may be echo or fluorogenic, or it may be filled with an echo or fluorogenic liquid or suitable medium, such as carbon dioxide or agitated saline. In its inflated state, it is preferred that the bladder is wide or thick enough to so  
20 that the endview of the bladder is visible in a short axis view of the mitral valve, as shown in Fig. 19, and that the bladder is long or high enough so that the anterior and posterior leaflets may seal against the bladder in systole.  
25

In addition, as shown in Fig. 20, the bladder 625 may be supported by a  
30 frame 626. The frame 626 may be comprised of any suitable material, such as nitinol, stainless steel, plastic or any combination thereof, of any consistent or variable flexibility, and any cross-sectional shape, such as round wire, hollow tube or flat ribbon. This material may be echo or fluorogenic or treated for such effects. In addition, the shape of the frame 626 may be of any suitable symmetrical or nonsymmetrical geometry,  
35 including but not limited to triangular, rectangular, circular, oblong, and single or multi-humped. A rectangular geometry is depicted in Fig. 20. In addition, the frame 626 may be expandable as shown in Figs. 21A-C. In the collapsed state, Fig. 21A, the bladder 625 and enclosed frame 626 may be inserted through a lumen in a guide catheter or interventional tool. When appropriately positioned, the frame 626 may be gradually expanded, Fig. 21B, to a desired geometry, Fig. 21C. It may be appreciated that the  
40 orientation element may function without inflation of the bladder 625 or with just the frame 625 and no bladder.  
45

Fourth, orientation may be assessed by visualization of flow patterns  
50 resulting from system or component position with respect to cardiac structures. As mentioned, the heart may be slowly beating throughout the tissue modification procedure.  
55

5 As the heart beats, blood may be flowing from the left atrium, through the mitral valve, to  
the left ventricle. Visualization of these flow patterns using Color Doppler  
Echocardiography may allow inferences as to how systems or components are positioned.  
10 For example, as shown in Figs 22A, if a thin planar structure 650 is inserted in the valve  
5 opening with its long axis perpendicular to the line of coaptation C, a higher level of  
regurgitation may result due to blood flow through the unsealed portions 651. If the  
structure 650 is inserted with its long axis along the line of coaptation C, as shown in Fig.  
15 22B, a lower level of regurgitation may result due to more adequate sealing of the valve  
leaflets LF against the structure 650. Thus, such a structure 650 or similarly designed  
10 device may be used as an orientation element.

## 20 VI. STABILIZATION

Before a valve or tissue modification or intervention is performed, it will  
usually be desirable to temporarily stabilize the interventional tool in relation to the a  
cardiac structure. By "stabilization" it is meant that the interventional tool will be  
25 somehow coupled to a cardiac structure so that any existing relative motion between the  
15 tool and the structure is lessened. Cardiac structures which may be utilized for coupling  
include the atrial walls, interatrial septum, valve annulus, valve leaflets, valve  
commisures, valve chordae, papillary muscles and ventricle walls, to name a few. Such  
30 stabilization is performed in order to facilitate a subsequent intervention. For example, an  
20 access catheter may be mechanically coupled to the valve or tissue surrounding the valve,  
such as the annulus or the chordae, and the interventional tool deployed from the catheter  
35 to perform a desired intervention, such as suturing, stapling, snaring, annuloplasty, RF  
tissue modification, or the like. The stabilization will usually be terminated after the  
particular valve modification is completed, but in some instances the stabilization could  
25 be terminated and redeployed multiple times at various points throughout the procedure.

40 The stabilization mechanisms may be separate from or integral with any  
part of the system or device. They may be removably or fixedly mounted on the  
guidewire, guide catheter, interventional tool and/or other device. Likewise, the elements  
45 may be components or parts of components of the device which provide one or more  
30 additional functions in the tissue modification procedure, such as steering, orientation  
assessment, grasping, coaptation, adjustment or fixation. Further the mechanisms may be  
atrial, ventricular or atrial-ventricular devices such that they may or may not cross the  
50



5 valve in the stabilization process. In particular, such mechanisms may be used to steer and/or orient the components and systems prior to or simultaneous with stabilization.

10 In the preferred embodiments, three general categories of stabilization mechanisms may be formed for descriptive purposes: 1) stabilization against the atrial  
5 septum, atrial walls or ventricle walls, 2) stabilization against the valve, and 3) stabilization against the chordae or papillary muscles. Stabilization against the atrial septum may be useful when approaching antegrade with atrial or atrial-ventricular  
15 devices. As previously described, an antegrade approach involves crossing from the right atrium RA to the left atrium LA by penetrating the interatrial septum IAS. This may be  
20 accomplished with a needle bearing catheter, which may then be exchanged for an introducer, guide catheter or similar catheter. Interventional tools may be introduced through this catheter for tissue modification treatment. To prevent movement of the  
25 catheter in an axial direction, a stabilization mechanism may be used to engage and lock the catheter to the interatrial septum. A preferred embodiment is shown in Fig. 23, which  
30 depicts a catheter shaft 660 having a distal balloon 661 and a proximal balloon 662 inflated on opposite sides of the interatrial septum IAS. Inflation of the balloons 661, 662 against the septum couples the shaft 660 to the septum and stabilizes the system. It  
35 may be appreciated that a number of components, such as disks, cages, balls, mesh, or other structures, may be used in place of one or more of the balloons to achieve a similar  
40 result.

45 Stabilization against the atrial septum may also be achieved by forming an introducer or guide catheter which is rigid through the interatrial septum and left atrium. Typically, such introducers or guide catheters are flexible along their length to facilitate  
50 introduction through the tortuous paths of the vascular system. In an antegrade approach as described, the catheter may be inserted through the interatrial septum with its distal end  
55 suspended in the left atrium. In the case of a flexible catheter, movements at the septum may not be translated linearly to the catheter tip. Therefore, there may be relative movement between the distal end and the portion passing through the septum. This may be reduced by coupling the distal end to the portion passing through the septum. In a  
60 preferred embodiment, the catheter shaft between and including the distal end and the portion passing through the septum may be made rigid. Referring to Fig. 24, the catheter shaft 670 may be comprised of stacked elements 671. The elements 671 may be domed disks or collar segments with domed ends which are mechanically coupled by a structure  
65 672. The structure 672 may connect the centers of the elements 671, as shown, in a

5 flexible manner so that the shaft 670 may be shaped in any desired geometry suitable for  
use in the tissue modification treatment. Once a desired shape is formed, the structure  
672 may be rigidified to hold the shape. Such rigidity may allow any movement of the  
10 interatrial septum to be translated to the distal end of the catheter shaft, thus coupling the  
5 catheter to the movements of the heart. This may improve stabilization of the devices and  
systems used in the tissue modification treatment. It may be appreciated that a variably  
rigid shaft as described may be utilized for coupling to any cardiac feature and may be  
15 used with or as part of any device component or device in the procedure. Thus, the  
feature may be utilized to lock any device component, catheter or tool into place once it  
10 has been manipulated into a desired shape. This may be useful in a variety of situations  
in addition to those mentioned above.

20 Stabilization against the valve may be most useful when approaching  
antegrade with atrial or atrial-ventricular devices, however it may also be useful when  
approaching retrograde with ventricular or atrial-ventricular devices. When approaching  
15 antegrade, stabilization may be most easily achieved by coupling one or more  
25 components of the device to the atrial walls, valve annulus, valve leaflets, and/or valve  
commissures.

30 Coupling to the atrial walls may be accomplished by a number of  
stabilization mechanisms. In each embodiment, structures such as wires, ribbons, mesh,  
20 cages or balloons extend outwardly from the device, contacting and applying radial force  
to the atrial walls. Such contact may couple the movements of the atrium with the device  
for stabilization. A preferred embodiment is shown in Fig. 25. Here, flexible wires 680  
35 bend out radially from the catheter shaft 681 with curved portions contacting the atrial  
walls AW. It may be appreciated that any number of wire patterns or means of extending  
25 from the shaft may be utilized, as mentioned above.

40 Coupling to the valve annulus may also be accomplished by a number of  
stabilization mechanisms, many of which include simultaneous coupling to other valve  
features, such as the leaflets and/or commissures. In preferred embodiments, such  
stabilization mechanisms may be comprised of loops, rings, wings, petals, arms, and the  
45 30 like. Coupling can be enhanced by varying surface friction and/or combining structures  
with vacuum. One or more of these mechanisms may be present, typically extending  
radially from a central shaft. When two elements are present, they are commonly placed  
50 90 to 180 degrees, preferably 120 to 180 degrees, apart around the central shaft. More  
than two elements are typically arranged in a radial pattern around the central shaft.

5 Structure, size, angle and arrangement may be adjustable to fit individual patient anatomy.

10 Examples of such embodiments are shown in Figs. 26-29. Referring to Fig. 26, a guide catheter 14 may have deployable adjustment wires 20 to serve as a  
5 stabilization mechanism. The wires 20 are typically attached at one end to the distal tip of the guide catheter 14 and may be advanced at their other ends so that they selectively deploy from the guide catheter to engage the mitral valve MV. The adjustment wires 20  
15 may act to stabilize or anchor the guide catheter relative to the mitral valve MV by coupling to the valve annulus, leaflets or commissures.

20 Similarly, the guide catheter 14 may have any number of stabilization elements, as illustrated in Figs. 27-29. As shown in Fig. 27, the stabilization elements may be comprised of a number of petals 22 arranged around the distal tip of the catheter 14. Similarly, the stabilization element may be a single large loop 25, as depicted in Fig.  
25 28. Alternatively, the interventional catheter 30 may have a plurality of stabilizing arms 34 (Fig. 29) which both position and anchor the distal tip of the interventional catheter 30 relative to the valve annulus. Usually, at least three stabilizing arms will be utilized, with four being illustrated, however any number may be used. The stabilizing arms 34 may be  
30 pre-shaped, resilient metal rods (for example, formed from nitinol or other shape memory or superelastic alloy), ribbons, tubes, polymers or composites thereof that may be  
20 selectively extended from the tip of the interventional catheter 30 to engage the valve annulus. The interventional catheter 30 of Fig. 29 is shown with a separately extendable interventional tool 36 which performs the desired valve or tissue modification, as  
35 described in more detail below. Such stabilization elements may preferably engage the annulus located about the mitral valve MV and apply forward pressure against the  
25 annulus to maintain contact and provide axial stabilization.

40 Stabilization may also be achieved by applying radial pressure to the commissures. As shown in Fig. 30, a pair of stabilization elements 32 may extend radially from a guide catheter 14 or interventional tool 30 to contact the commissures. The distance between the elements 32 may be equal to or slightly greater than the  
45 distance between the commissures to apply radial force against the commissures. The stabilization elements 32 may be comprised of any suitable material, such as nitinol, stainless steel, plastic or any combination thereof, of any consistent or variable flexibility, and any cross-sectional shape, such as round wire, flat ribbon or hollow tube. As shown  
50 in Figs. 31A-31D, the shape of the stabilization element may be of any suitable

5 symmetrical or nonsymmetrical geometry, including but limited to triangular (Fig. 31A),  
rectangular (Fig. 31B), circular, oblong, double-humped (Fig. 31C) or single-humped  
10 (Fig. 31D). It may be appreciated that such stabilization mechanisms may also serve in  
orientation assessment, particularly as the frame 626 (Fig. 20) previously described.

5 Thus, they may be echo or fluorogenic or treated for such effects. In addition, it may be  
appreciated that such stabilization elements may be passive, i.e., pre-sized and shaped to  
fit the patient anatomy so that they engage the valve annulus without adjustment, or may  
15 be active so that they can be used to steer the guide catheter as previously described.

A number of stabilization mechanisms apply both radial and axial pressure  
10 to the valve for stabilization. For example, the double-humped element, shown in Fig.  
31C, has a superior hump 700 which may protrude into the left atrium, contacting the  
superior aspect of the annulus and possibly the left atrial wall, and an inferior hump 701  
20 which may protrude into the left ventricle, contacting the inferior aspect of the annulus  
and possibly the left ventricle wall or chordal tissue. The superior hump 700 may apply a  
downward axial force on the annulus and the inferior hump 701 may apply an upward  
25 axial force. The waist 702 between the humps may be dimensioned or adjustably sized to  
fit between the commissures and to apply a radial force on the commissures. Similarly, a  
single-humped element, shown in Fig. 31D, may provide similar stabilization without the  
added support from the protruding inferior hump. Additionally, this design may be easier  
30 to position in the mitral valve.

The last general category of stabilization mechanisms for descriptive  
35 purposes is stabilization against the chordae. Stabilization against the chordae may be  
most useful when approaching retrograde with ventricular or atrial-ventricular devices.  
Coupling to the chordae may be useful in stabilization for tissue modification to the  
25 valve, the chordae, the annulus or a combination of these. When modifying the valve, the  
contact with the valve structures (typically grasping of the valve leaflets) may still be  
40 necessary. However, when modifying the chordae, additional contact (such as grasping  
the chordae) may not be necessary since the stabilization methods may include this step.  
Therefore, stabilization against the chordae will be discussed in Section VIII Grasping.

## 30 VII. IMMOBILIZATION

Immobilization refers to substantially retarding or diminishing the motion  
of the cardiac structures or intermittently or temporarily stopping the cardiac cycle. This  
50 may be accomplished with a variety of methodologies. First, drugs may be injected to

5 temporarily slow or stop the cardiac cycle. Such drugs may include but are not limited to  
esmolol, adenosine, isoflurane and transarrest mixture, with or without electrical pacing.  
Likewise, induced atrial fibrillation may interrupt the cardiac cycle.

10 Mechanical immobilization of the valve can be effected in a variety of  
5 ways. Most simply, valve action can be diminished or stopped by raising the pressure in  
the associated ventricle to a pressure above that in the atrium during diastole. For  
example, a suitable liquid can be infused into the ventricle to raise the intraventricular  
15 pressure, or the aortic valve could be temporarily incapacitated allowing aortic  
regurgitation and raising the ventricular diastolic pressure. Alternatively, interventional  
20 tools and/or catheters carrying such tools may simply be mechanically stabilized against  
the valve, valve annulus, valve commissures, ventricular wall, atrial wall, generally as  
described above.

Mechanical valve immobilization will usually involve more interaction  
with the valve than simple stabilization. Immobilization will usually involve either  
25 15 capture and immobilization of either or both valve leaflets (or all three valve leaflets in  
the case of a tricuspid valve) or capture and immobilization of the chordae. For example,  
balloons or mesh cages may be used and placed under one or both leaflets to hold them  
partially closed. By temporarily immobilizing or adjusting the valve action, such as  
30 changing the point of coaptation, it is possible to see if a particular modification will be  
sufficient to treat the regurgitation. For example, by temporarily grasping the valve  
20 leaflets at a particular point and holding the leaflets together, it can be determined  
whether a permanent suturing, stapling, or other affixation at that point will achieve a  
35 sufficient reduction in regurgitation. When the heart is beating, valve regurgitation can  
be examined in real time via conventional imaging techniques, such as TEE. If the  
25 temporary valve modification appears sufficient, it can then be made permanent using any  
one of a variety of interventional techniques.

#### 40 VII. GRASPING

Valve or tissue modifications or interventions most commonly require  
45 grasping a portion of the valve or tissue to be modified. Such grasping may be useful in  
30 adjusting tissues (such as coapting valve leaflets) for appropriate modification, checking  
the positioning of the tissues for improved biological function, and stabilizing or  
immobilizing the tissue for the modification procedure. As previously described, such  
50 grasping may also be useful to stabilize another tissue which will be modified in the

5 procedure, such as the grasping the chordae to stabilize the valve for valve modification.  
Since the most common procedures may involve valve modification or chordal  
modification, grasping of these cardiac structures will be discussed. However, it may be  
10 appreciated that described grasping devices, systems and methods may apply to any  
5 cardiac or other structure.

A. Chordal grasping

Grasping of the chordae may involve capturing and anchoring the chordae,  
15 as illustrated in Figs. 32-40. As shown in particular in Figs. 32A and 32B, a guide  
catheter 40 can deploy a first capture coil 60 and a second capture coil 62 through a pair  
10 of deployment catheters 64 and 66, respectively. The coils will be positioned while  
visualizing so that the first coil 60 captures chordae attached to a first valve leaflet LF and  
20 coil 62 captures chordae attached to a second valve leaflet LF. The capture coils will  
typically be elastic wires, preferably composed of a superelastic material such as nitinol,  
which are delivered through the deployment catheters in a straightened configuration.  
15 When they are advanced out of the deployment catheters, the capture coils will assume a  
helical or other configuration that can be advanced into and entangle the chordae.

The coils 60 and 62 may then be brought together laterally preferably  
30 coapt the leaflets LF together by advancing a retaining ring 68 which is secured at the  
distal end of a deployment wire 70, as illustrated in Fig. 32B. The leaflets are thus  
20 brought together and immobilized for a subsequent intervention. Alternatively, if  
immobilization via the coils 60 and 62 is sufficient in itself, it will be possible to make the  
deployment permanent. It is a particular advantage of the temporary immobilization that  
35 the valve action can be examined via the real time imaging techniques to see if  
regurgitation has been adequately addressed. If it hasn't, the coils can be redeployed or  
25 the relative positions of the two coils 60 and 62 can be changed until an adequate pair has  
been effected.

It will be appreciated that if a subsequent interventional step is required, it  
can be made from either an antegrade or retrograde approach. A variety of specific  
45 interventional techniques are described in detail hereinbelow.

30 An antegrade approach for deploying a single chordae snare 74 and  
optionally securing a suture loop about the captured chordae is illustrated in Figs. 33A  
and 33B. A guide catheter 14 deployed over the leaflets LF of the mitral valve MV may  
be deployed as described previously. A pair of deployment catheters 76 and 78 are  
50 advanced from the distal end of the guide catheter 14 and observed in real time via any of

5 the imaging techniques described previously. The pre-shaped snare 74 is advanced out of  
the first deployment catheter 76 and is advanced through both of the chordae CT, as  
illustrated in Fig. 33A. A capture loop 80 is advanced from the second deployment  
10 catheter 78 and positioned so that it lies in the path of the pre-shaped snare 74 as it  
5 is advanced through the chordae CT. After a capture tip 82 passes through the capture loop  
80, the loop can be tightened to secure to the capture tip 82 and draw the tip into the  
second deployment catheter 78. The capture tip 82 is attached to an end of a length of  
15 suture 84 (Fig. 33B) which runs back through a lumen in the snare 74. In this way, the  
suture may be pulled into the second deployment catheter 78, while the snare 74 is  
10 withdrawn back into the first deployment catheter 76, leaving only the suture in place  
grasping both the chordae. By then tying or otherwise securing the suture together into a  
20 permanent loop through the chordae, the coaptation of the valve leaflets LF can be  
modified in a desired way. As with the previous embodiments, a particular advantage of  
this approach is that the valve coaptation can first be viewed using the real time imaging  
25 capability to assure that valve regurgitation is adequately addressed before making the  
chordae capture permanent.

An alternative technique for deploying suture to capture chordae CT is  
illustrated in Fig. 34. First deployment catheter 90 (positioned through a guide catheter  
30 which is not shown) is positioned through the opening between valve leaflets LF. A  
20 balloon 93 at the distal end of chordae snare 92 is extended through the chordae, as  
described previously. The balloon 93 is inflated and floated through the mitral valve  
during regurgitation. The balloon will pass through the previously deployed capture  
35 snare 95. Alternatively, the chordae snare 92 could be shaped so that it will encircle the  
chordae and then pass outwardly through the valve opening and into the previously  
25 deployed capture snare 95.

40 A chordae stabilization catheter 100 which is particularly suited for a  
retrograde approach is illustrated in Fig. 35. The catheter 100 includes a catheter body  
102 having a pair of lumens 104 and 106 extending from a proximal end (not shown) to a  
distal end which is illustrated in Fig. 35A. The main lumen 104 extends fully to the distal  
45 tip of the catheter body 102 and a chordal snare 108 is slidably received in the lumen.  
30 The snare 108 has a loop pre-formed over its distal end so that, when extended from the  
catheter 100, it will assume the shape shown in Fig. 35. The loop has a diameter  
generally in the range from 3 mm to 20 mm and is shaped so that it will evert backwardly  
50 into a secondary loop formed by a capture snare 112. The capture snare 112 is disposed

5 in the secondary lumen 106 and emerges from an opening 114 space proximally from the distal end of the catheter 100. The distal tip of the capture snare 112 is fixed at an anchor point 116 in the distal tip of the catheter body 102. Thus, by extending and retracting the capture snare 112, the capture loop can be moved between the position shown in full line and broken line.

10 Referring now to Figs. 36A and 36B, use of the catheter 100 for capturing and stabilizing chordae CT will be described. The catheter 100 is introduced in a retrograde direction (although antegrade would also be possible), typically through a guide catheter 40 as generally described above. Under direct (e.g., fluoroscopic) observation, the distal end of the catheter 100 will be guided to a position generally within the chordae CT, as illustrated in Fig. 36A. The chordae snare 108 will then be extended from the distal tip so that it passes through and becomes entangled with the chordae CT attached to both of the leaflets LF. The distal tip of the chordal snare 108 will eventually pass through the loop defined by the capture snare 112, also as illustrated in Fig. 36A. The capture snare will then be tightened to hold the distal tip of the chordae snare 108, and the chordae snare then retracted so that the loop of the snare which passes through the chordae will be tightened, generally as shown in Fig. 36B. Generally, the catheter 100 will not be intended for permanently affixing the chordae CT. Instead, immobilization of the valve leaflets LF will be intended to facilitate a subsequent treatment step, as described hereinafter. Use of the retrograde approach for immobilizing the chordae CT will be particularly advantageous when used with antegrade interventions.

35 The catheter of Fig. 35 could, however, be modified to facilitate performance of retrograde interventions while the chordae are stabilized. As shown in Fig. 37, the catheter 120 includes a catheter body 122 which is generally the same as that shown for catheter 100 in Fig. 35 (with common components being given identical reference numbers), except that a third working lumen 124 is provided. The working lumen 124 can be used to deliver and position a wide variety of interventional tools for performing at least most of the specific interventions described elsewhere in this application. The catheter 120 will, of course, be particularly useful for performing interventions which rely on retrograde stabilization of the chordae CT of the type provided by the catheter. For example, the lumen 124 may be used to position an RF energy delivery tool for heating the chordae to cause shrinkage, as described in more detail below. Alternatively, the working lumen 124 could be used to position a chordae stabilization coil 130, generally as described in Figs. 39A and 39B. The coil is typically a



5 helical filament having a secondary helical structure comprising, for example, three major loops. The coil may comprise an inner element composed of a shape memory material, such as nitinol, inserted into an outer coil 132 made of a radiopaque material, such as a platinum alloy. The shape memory coil 134 is formed into a "stacked coil" configuration  
10 (with no space between adjacent windings of the coil) and then programmed so that it will assume the stacked coil configuration at a temperature slightly above body temperature. The coil assembly 130 is formed by heat treating the platinum 132 to a diameter D1 and length L1, as shown in Fig. 39A. The shape memory coil 134 is then stretched to a near-linear configuration and inserted into the platinum coil 132, and the two are coupled at the  
15 end. Upon heating, the shape memory coil contracts back into its tightly stacked coil shape, compressing the platinum coil 132, and causing the entire assembly 130 to assume a smaller diameter D2 and length L2, as shown in Fig. 39B. The coil 130 may be delivered using a pusher catheter through the working lumen 124 so that it deploys within and entangles the chordae CT, as shown in Fig. 40. The pusher catheter (not shown)  
20 could be configured similarly to embolic coil delivery catheters, such as those described in U.S. Patent Nos. 5,226,911; 5,234,437; 5,250,071; 5,261,916; 5,312,415; 5,350,397; and 5,690,671, the full disclosures of which are incorporated herein by reference.

30 B. Valve leaflet grasping

Valve leaflet grasping may be accomplished using a number of methods,  
20 most commonly the following three: 1) pinching, 2) partially or fully penetrating or piercing, and 3) the use of suction or vacuum. Pinching involves grasping the surface or edge of the leaflet without penetrating the tissue. This may be accomplished by an antegrade or retrograde approach using atrial, ventricular or atrial-ventricular devices. It  
35 may be appreciated that although the following embodiments are examples which are described relative to a specific approach (antegrade or retrograde), each device or  
25 component may be used or adapted to be used in all approaches.

In preferred embodiments, depicted in Figs. 41-43, pinching of the valve  
40 leaflets LF can be achieved, for example, by using a grasping catheter introduced in a retrograde direction to temporarily capture the free ends of the valve leaflets LF. It may  
45 be possible to use a simple two-jaw tool at the distal end of a catheter to capture both opposed leaflets. Such a two-jaw tool 710 is depicted in its open position in Fig. 41A. In this position, opposing jaws 711 may be positioned on opposite sides of the free ends of the valve leaflets LF. In its closed position, depicted in Fig. 41B, the leaflets may be  
50 drawn together and pinched to immobilize the valve. Although this may be adequate, it

5 may be preferred to use a three-jaw capture tool as shown in Figs 42-43. The catheter  
140 can be delivered through a guide catheter generally as described above. The catheter  
includes a tool 142 at its distal end. Tool 142, as best shown in Fig. 42B, includes a fixed  
10 center jaw 144 and a pair of pivotable outer jaws 146 and 148. The jaws 146 and 148  
5 may be independently opened to a "capture" position as shown in broken line in Fig. 42B.  
Actuation of the jaws 146 and 148 may be achieved in a variety of conventional manners,  
including pull wires, push wires, inflatable balloons, heat memory alloy motors, and the  
15 like. By independently opening and closing the capture jaws 146 and 148 against the  
fixed jaw 144, the valve leaflets LF can be captured independently.

10 As shown in Fig. 42A, a first leaflet LF can first be captured. The catheter  
140 can then be manipulated and positioned, typically under real time imaging, to capture  
20 the second leaflet LF, as shown in Fig. 43. It will be appreciated that independent capture  
of the leaflets greatly facilitates the procedure. Use of a single pair of capture jaws  
requires that the leaflets be captured at the instant when they are properly opposed. In the  
25 case of prolapsed valves, such an instance may never occur. Once captured and  
immobilized, as shown in Fig. 43, the valve leaflets can then be modified in any one of a  
variety of ways, as described elsewhere in the application.

30 Additional embodiments, depicted in Figs. 44-46, involve pinching of the  
valve leaflets LF by using a grasping catheter introduced in an antegrade direction to  
20 temporarily capture the surfaces or the free ends of the valve leaflets LF. Referring to  
Figs. 44A-44D, the valve leaflets LF may be pinched between a superior loop 720 and an  
inferior loop 721. In a preferred embodiment, the grasper is comprised of a nitinol flat  
35 ribbon heat set in the shape of double loops 720, 721. The ribbon may be mounted on a  
series of three coaxial shafts, an interior shaft 725, a central shaft 726 and an exterior  
25 shaft 727. The distal end of the ribbon may be attached to the distal end 730 of the  
interior shaft 725, a midportion of the ribbon may be attached to the distal end 731 of the  
40 central shaft 726, and the proximal end of the ribbon may be attached to the distal end  
732 of the exterior shaft 727. One or more ribbons may be mounted on the coaxial shafts;  
in this example, two ribbons are shown 180 degrees apart. When extended, as shown in  
45 Fig. 44A, the grasper may be pulled flat against the shafts 725, 726, 727 for ease of  
insertion through a guide catheter or tool and into a desired position between the valve  
leaflets LF. When the central shaft 726 is retracted or the exterior shaft 727 advanced, as  
50 shown in Fig. 44B, the superior loops 720 may extend radially from the shafts. The  
superior loops 720 may rest on the superior surface of the valve leaflets LF in the atrium,

5 as shown in Fig. 44D. In this position, the superior loops 720 may aid in orientation  
assessment, as the superior loops may be echo or fluorogenic and may be easily visible in  
relation to the cardiac structures or other devices or components. When positioned in a  
desired location, the interior shaft 725 may then be retracted, as shown in Fig. 44C, to  
10 extend the inferior loops 721 radially from the shafts. The inferior loops 721 may be in  
contact with the inferior surface of the valve leaflets LF in the ventricle. Thus, the valve  
leaflets LF may be pinched between the inferior loop 721 and superior loop 720. It may  
also be appreciated that the inferior loops 721 may be deployed prior to the superior loops  
15 720.

10 Referring to Figs. 45A-45B, the valve leaflets LF may be pinched between  
a superior roller 750 and an inferior roller 751. As shown in Fig. 45A, the rollers 750,  
20 751 may be mounted on a shaft 755 and connected by a pull actuation wire 756. The  
rollers 750, 751 may be serrated or surface treated in a directional pattern to facilitate  
grasping of the valve leaflets LF. To grasp a leaflet LF, the rollers 750, 751 may be  
25 placed against the surface or free edge of the leaflet LF. Pulling of the actuation wire 756  
may rotate the superior roller 750 and inferior roller 751 toward each other. This may  
draw the leaflet LF between the rollers 750, 751, as shown in Fig. 45B. Thus, the leaflets  
LF may be individually grasped for treatment.

30 Referring to Figs. 46A-46B, the valve leaflets LF may be pinched between  
20 a pair of flat coils 770. In a preferred embodiment, each coil 770 may be comprised of  
nitinol flat ribbon heat set in the shape of a coil. As shown in Fig. 46A, the coils 770 may  
be linked together with opposing curvature by a clip 772. Movement of the clip 772  
35 along the coils 770 may uncurl the coils 770 to a straightened configuration. As shown in  
Fig. 46B, this may also be accomplished by a catheter shaft 773 placed over the coils  
25 770. In the straightened position, the coils 770 may be inserted between the valve leaflets  
LF in an atrial-ventricular position so that the distal ends 775 of the coils 770 are in the  
40 ventricle. As the shaft 773 or clip 772 is retracted, the coils 770 may begin curling  
radially beneath the valve leaflets LF and upwardly so that the distal ends 775 of the coils  
770 contact the inferior surface of the valve leaflets LF. Similarly, if the coils 770  
45 30 continue curling, a portion of the flat ribbon proximal to the distal end 775 may contact  
the valve leaflet. In this manner, the leaflets may be grasped for treatment. Such a  
grasping device may also serve as a fixation device with the pair of coils 770 left in place,  
50 as will be described in a later portion of the application.

5 A valve or tissue structure may also be grasped by atraumatic partial or  
full penetration or piercing. This may be accomplished with a variety of grasping  
mechanisms. Preferred embodiments include one or more prongs extending from an  
10 interventional tool in an arrangement to grasp a specific structure. Specifically, three  
5 opposing prongs may extend from a grasping sheath with distal ends configured to pinch,  
partially penetrate or pierce. Such ends may be pointed or may be soft, as in the case of  
rounded, urethane coated or solder coated ends. Referring to Fig. 47A, the opposing  
15 prongs 800 may be retracted into a grasping sheath 801 to hold the prongs 800 in a closed  
configuration. It may be preferred to orient the device to a desired position in this  
10 configuration. When the target tissue has been located, the prongs 800 may be extended  
to grasp the tissue structure, as shown in Fig. 47B. This may be accomplished by either  
20 extending the prongs 800 axially or retracting the grasping sheath 801. The target tissue  
may be pinched, partially penetrated or pierced with the prongs 800 in this configuration,  
or such action may be facilitated by closing or partially closing the prongs 800 as  
25 previously depicted in Fig. 47A. Alternatively, the prongs 800 may be attached to or  
integral with a prong-tipped tube 802, as shown in Fig. 47C. Such a design may be more  
conductive to the insertion of tools or fixation devices for further treatment steps, such as  
tissue modification. Tools or devices may be inserted through a lumen in the prong-  
30 tipped tube 802, depicted by arrows 804, for use at or near the grasping location.  
20 Similarly, tools or fixation devices may be inserted through a lumen in a hollow prong  
806, as depicted in Fig. 47D. Here, one or more prongs 806 may be hollow, and the  
remaining prongs 808 may be comprised of solid wire or a suitable material. Tools or  
35 devices may be inserted through a lumen in the hollow prong 806, depicted by arrows  
810, for use at or near the grasping location. Prongs, hollow or solid, may be made from  
25 stainless steel, NiTi, plastic or other suitable material. Additionally, they may be coated  
or coiled to enhance visibility. Likewise, the geometries of the prongs may be varied to  
40 facilitate grasping of the desired amount of tissue. And, the distal tip sharpness and  
surface finish can be varied to establish the amount, if any, of piercing.

45 In addition to directly engaging the valve leaflets to effect stabilization  
30 and/or immobilization with the grasper devices described above, the present invention  
may also employ a catheter or other tool having vacuum or suction applicators to  
temporarily capture the valve leaflets. As shown in Fig. 48, a catheter 812 comprises a  
50 shaft having a pair of vacuum applicator rods 813 and 814. Usually, the vacuum  
applicator rods 813 and 814 will comprise separate shafts which may be axially translated

5 relative to the main shaft of the catheter. Further optionally, the shafts could be articulated or otherwise manipulable so that they can be independently positioned relative to the valve leaflets or other tissue structures once the catheter 812 is in place. The vacuum applicators have one or more apertures to permit contact and adherence to tissue  
10 when the applicators are attached to external vacuum sources. Usually, the shaft will be placed across the valve, either in an antegrade or retrograde fashion, and the applicators positioned to grasp and manipulate the valve leaflets. Optionally, the catheter 812 may comprise additional stabilizing and/or steering wires of the type previously described. For example, a steering wire 815 (and optionally a second steering wire on the opposite  
15 side) may be provided for engaging against the valve commissures to permit positioning of the catheter with respect to the valve leaflets. The vacuum applicators would further be independently positionable to engage the valves in the desired fashion. Using this catheter, the leaflets can be grasped and the competency of the valve evaluated using the methods described previously. The valve adjustment can then be effected using any of  
20 the interventional approaches described herein. Further, it may be appreciated that in each embodiment, timing of grasping may be facilitated by the use of gating with the patient's EKG, pressure waves of the cardiac cycle, audio heart sounds, electronic pressure or contact sensors on the graspers.

#### 30 VIII. COAPTATION, ADJUSTMENT AND EVALUATION

20 Once the valve leaflets, chordae or tissue structure is grasped by an interventional tool, the tissue may be manipulated to achieve a desired result, such as improvement in valve function. Such manipulation may occur during the grasping step, or it may require a separate step following grasping. In the case of leaflet modification, valve leaflets may be coapted or brought together and held in a preferred apposition. The  
35 valve function may then be evaluated for indications of improved valve function, such as reduced regurgitation. If further improvement is desired, the valve leaflets may be additionally manipulated or adjusted. Adjustment should primarily occur in a superior/inferior (up/down) motion in order to bring the leaflets to a final positioning where regurgitation is minimized. During adjustment, one or both leaflets may be  
40 released and recaptured with new positioning. After the final evaluation, the valve leaflets may be fixated in the desired position by an appropriate fixation device. In the case of chordae shortening or other tissue modification, similar steps may be taken.

## IX. TISSUE MODIFICATIONS

Repair of atrioventricular or other cardiac valves according to the present invention is effected by modifying the valve or a supporting tissue structure in some way to affect blood flow through the valve during a phase of the cardiac cycle, for example to permit blood flow through the valve during diastole when the associated ventricle is filling with blood but which inhibits or prevents blood regurgitation back through the valve during systole. A number of techniques for modifying the valve closure by capturing or grasping the chordae attached to each valve leaflet have been described above. These techniques are often used just for valve grasping and/or coaptation and adjustment prior to a separate valve modification step, but they may also be made permanent to provide the final valve modification. Other techniques for more directly modifying the leaflets or other supporting structures of the atrioventricular valves will be described in this section. These techniques may be utilized either with or without the valve grasping and/or coaptation and adjustment techniques described above. For purposes of simplicity, however, the following methods will generally be described without specifically illustrating such grasping, coapting and adjustment approaches, focusing primarily on the methods and devices involved with fixation. In addition, it may be appreciated that although the following embodiments are examples which are described relative to a specific approach (antegrade or retrograde), each device or component may be used or adapted to be used in all approaches. Further, although devices and methods are described for fixating specific tissues, such as valve leaflets or chordae, such devices and methods may be used for any cardiovascular tissues and the like.

### A. Fixation of Valve Leaflets

Suture can be delivered through the valve leaflets and then tied in a manner analogous to an open surgical procedure. In one embodiment, a suturing tool 200, shown in Fig. 49, may be positioned at the distal end of an interventional catheter. The interventional catheter will usually be advanced in an antegrade direction (i.e., from above the mitral valve), either directly through a guiding catheter or through a working lumen in a stabilization catheter. The tool 200 carries a length of suture 202 attached to a pair of needles 204 at either end thereof. The suture may be comprised of conventional suture material or of wire, typically stainless steel, nitinol or other material. The needles are held on a reciprocating shaft 206 disposed within a lumen of a retrieval sheath 208. The tool 200 can be positioned to capture the opposed free ends of the mitral valve

5 leaflets LF, generally as shown in Fig. 49. The needles can then be advanced through the  
leaflets LF by drawing the shaft 206 toward the sheath 208 so that the needles 204  
penetrate the leaflet and are captured in needle receptacles 210 formed in the sheath 208.  
10 The sheath can then be withdrawn. A knot can be tied in the suture, and the knot then  
5 advanced through the associated catheter to tighten over the valve leaflets. The tool 200  
can carry two, three, four, or even more lengths of suture which may be simultaneously or  
sequentially introduced into the valve leaflets in order to permit multiple suture loops to  
15 be placed. The resulting tied suture loops will be similar to the "bow tie" sutures placed  
in open surgical procedures which have been described in the medical literature as  
10 described above.

20 The need to place and draw long lengths of suture through the valve  
leaflets can, however, be deleterious to the fragile leaflet structures. Thus, alternative  
needle and suture devices which rely on mechanical fasteners in relatively short suture  
lengths may be preferred. In one embodiment, a hollow suturing coil 1300, shown in Fig.  
25 49A, may be positioned at or near the distal end of an interventional catheter. The  
15 suturing coil 1300 may be comprised of any material of sufficient rigidity to pierce and  
penetrate through valve leaflets LF, such as stainless steel, various shape memory or  
superelastic materials, metal alloys and various polymers, to name a few. The hollow  
30 suturing coil 1300 may contain a suture 1302 comprised of conventional suture material  
20 or of wire, typically stainless steel, nitinol or other material. The suture 1302 may be  
secured at the tip 1304 of the coil 1300 with a toggle rod 1305. After the valve leaflets  
LF have been grasped and coapted, the suturing coil 1300 may be advanced in a  
35 corkscrew fashion through the valve leaflets LF, as shown in Fig. 49A. Though such  
advancement is shown from above, advancement may be made from any direction  
25 through any number and configuration of valve leaflet layers. When advancing, the  
40 sharpened tip 1304 of the coil 1300 may pierce through the leaflets LF any number of  
times. It may be appreciated that such corkscrew piercing may be made through the  
middle portions of the leaflets such that a pierce is made at each half-rotation, or the  
piercings may be made along the edges of the leaflets such that a pierce is made at each  
45 30 full-rotation, to name a few.

Once the coil 1300 has advanced to a desired location, the toggle rod 1305  
may be secured against a leaflet LF to hold the suture 1302 in place. At this point, the  
50 coil 1300 may be removed by retracting the coil 1300 in a reverse corkscrew fashion, as  
depicted in Fig. 49B, leaving the suture 1302 behind. Since the coil 1300 may be much

5 larger in diameter than the thickness of the leaflets (to aid in placement), the suture 1302  
may be loose-fitting and the valve leaflets LF insufficiently modified. The suture 1302  
may then be tightened, as shown in Fig. 49C, so that the suture 1302 holds the leaflets LF  
10 together in a desired configuration. This may be aided by the use of a soft-tipped catheter  
5 1306 which may be advanced to contact the surfaces of the leaflets LF when tightening to  
prevent the leaflets LF from prolapsing. Once the suture 1302 is sufficiently tight, a  
restrictive collar 1308 may be deployed from the catheter 1306 or another device to  
15 secure and terminate the suture 1302. Such a restrictive collar 1308 may be comprised of  
any suitable material, such as heat-shrink tubing, nitinol shape-memory or superelastic  
20 coil or the like. Thus, this embodiment eliminates the need for needle passers and needle  
receivers providing a simplified method of valve leaflet fixation.

20 Alternatively, referring to Figs. 50 and 51, a short length of suture 220  
may be positioned using a curved needle 222 which can be extended from the distal tip  
224 of an interventional catheter 225. The needle 222 is formed from an elastic material,  
25 such as a shape memory alloy, and may be constrained in a generally straightened  
configuration within the catheter 224. When extended, as shown in Fig. 50, it assumes a  
curved shape so that it may be advanced through the atrioventricular or other cardiac  
valve leaflets LF, as shown in Fig. 51. A distal anchor 226 is secured to the distal end of  
30 the suture 220 while a slideable, locking anchor 228 is placed over a portion of the suture  
20 located proximally to the distal anchor 226 as shown in Fig. 50. The catheter 225 may be  
advanced to the valve leaflets LF in a retrograde approach, as shown in Fig. 51, using a  
guide catheter 40, as generally described above. The distal end 224 of the catheter 225 is  
35 positioned adjacent to the underside of a valve leaflet, and the needle 222 then advanced  
outwardly from the distal tip so that it passes through both valve leaflets.

25 In order to assure that the valve leaflets are in a proper orientation prior to  
needle advancement, the valve leaflets may be coapted and observed using any of the  
40 techniques described previously. After the needle has been advanced through the leaflets  
LF, a deployment sleeve 230 is advanced to release the slideable anchoring catheter 228  
from the needle and advance it toward an underside of the valve leaflet LF. As the anchor  
45 228 approaches the valve leaflet, tension on the suture 220 will pull the distal anchor 226  
from the needle. The deployment sleeve 230 can be advanced sufficiently to draw the  
two anchors 226 and 228 together on opposite sides of the valve leaflets, as seen in Fig.  
50 52. The suture can then be tied off or, alternatively, locked in place using a mechanical  
lock 232. If the suture is comprised of a malleable wire, as previously described, the wire



5 may be twisted together. In either case, the suture is then severed and the catheter 225 withdrawn.

10 The anchors 226 and 228 shown in Fig. 50 are generally oval shaped and have a length dimension which is greater than the width of the needle used to introduce them. Thus, when pulled laterally, they can seal against the opposed surfaces of the two valve leaflets. In some instances, however, it will be desirable to have anchors which are capable of expanding to a much larger dimension to assure that they do not pull through the relatively fragile tissue of the leaflets. An exemplary expansible anchor 240 is shown in its collapsed configuration within a needle 242 in Fig. 53 and its expanded configuration in Fig. 54. The anchor 240 is connected to a length of suture 244 and could be used with a similar slideable, expansible anchor (not shown) analogous to the non-expansible anchor 228 of Fig. 50.

15 Additional expansible anchors may be seen in Figs. 55A and 55B. In this embodiment, the anchor is comprised of an expanding randomly oriented wire coil. The coil is made from a shape memory nitinol wire that is annealed (heat set) in a straight configuration and then coiled. As shown in Fig. 55A, different sections 820, 821 of the coil may be processed to have different properties by varying the diameter and tension in the coil along its length. When the coil is heated to a specified level ( $T_1$ ), such as with RF energy, a designated portion 821 of the coil will become a randomly oriented mass of wire 824 with self-locking struts to prevent disentanglement. When the coil is heated to a different specified level ( $T_2$ ), a different designated portion of the coil 825 will become randomly oriented. As each portion of the coil 824, 825 expands and changes shape, a full entanglement of the coils is allowed to occur, effectively compressing and fixing the two halves 824, 825 of each coil together. The coil may be introduced through the valve leaflets LF with the use of a shape memory, super elastic or heat/current activated needle introducer 826. Once the valve leaflets LF are pierced, an anchor 824 may be activated and deployed distally. The introducer 826 may then be retracted to the proximal side of the second leaflet LF2 and the second anchor (not shown) may be deployed in the same manner. The amount of tension between the anchors 824, 825 may be affected with the shape memory or super elastic properties of the expanding anchor. It may be appreciated that the heat activated expanding coil may alternatively take other forms, such as a wire mesh, for example. Additional expansible anchors may be in the form of inflatable chambers filled with a liquid that may optionally partially or fully solidify.

5 Yet another form of detachable anchor attached to a length of suture is illustrated in Figs. 56 and 57. Fig. 56 is a front view, while Fig. 57 is a side view of the same structure. A self-penetrating anchor 260 attached to a length of suture 262 is carried on a pair of rods 264. The rods are mounted within an open lumen of a deployment  
10 catheter 266. The anchor 260 can pivot on a detent structure 268 formed between the distal ends of the deployment rods 264. The anchor has a sharpened distal tip 270 which permits the anchor to be directly penetrated through the valve leaflet tissue when the rods are extended from the catheter 266.

Referring now to Fig. 57, the catheter 266 may be deployed over the  
10 leaflets LF of the mitral valve MV in an antegrade direction through a guide catheter 14 as generally described above. The catheter 266 can be used to deliver a pair of the anchors 260 sequentially. As shown in Fig. 58, a first anchor 260a has been deployed through a first leaflet and a second anchor 260b has just been placed through the second leaflet. The anchors 260a and 260b are deployed by pushing them through the leaflet  
20 tissue while the sharpened tip 270 remains generally in a distal or forward direction. After passing through the tissue, the anchor 260a/260b can be turned, either by pulling back on the deployment rods 264 or by pulling backwardly on the suture 262. The two ends of suture 262 can then either be tied or fastened using a mechanical fastener in order to draw the opposed leaflets into proper apposition.

Referring now to Figs. 59 and 60, a deployment catheter 290 having a  
20 needle 280 with sharpened distal tip 282 can be used to place suture loops in individual valve leaflets. A needle 280 is carried on a pair of actuator rods 284 with a length of suture 286 attached to the needle. The needle 280 is first passed through the leaflet in a generally axial orientation with respect to the catheter 290. After passing through the  
35 leaflet from a guide catheter 14, as shown in Fig. 60, the needle is canted at an angle from 20° to 30° and passed back through the leaflet at a different position. A locking groove 288 on the needle is captured on a bar 292 in the distal end of the catheter 290. The needle 280 may thus be detached from the rods 284 to pull suture 286 in a loop back through the leaflet. This way, loops of suture may be placed successively through both  
40 leaflets LF of a mitral valve MV, as shown in Fig. 60. The suture loops may then be tied off, connected with fasteners, fused together using RF, microwave or ultrasound energy, or otherwise secured to close the valves together in a desired apposition.

50 In addition to sutures and suture-based devices, as just described, opposed points on the valve leaflets and/or chordae can be attached with a variety of staples and

5 tissue-penetrating fasteners. The staples and other fasteners can be delivered through guide catheters, generally as described above, and may be positioned during or after valve grasping, coaptation and adjustment, also as described above.

10 Referring now to Figs. 61A and 61B, staple applying catheter 300 is  
5 schematically illustrated. Typically, the leaflets LF of a mitral or other atrioventricular valve will first be accessed by any of the techniques described above. The catheter 300 will then be introduced in a retrograde fashion, for example, as illustrated previously. A  
15 staple 302 is held in an open position at the distal tip of the catheter 300 and has a generally W-shaped profile with two recesses for receiving each of the leaflets LF, as  
10 shown in Fig. 61A. After proper positioning is confirmed visually, the staple 302 may be closed over the leaflets so that the tips penetrate opposed points on each leaflet by pulling  
20 on an actuator cord 304, as shown in Fig. 61B. The actuator cord can then be detached and the catheter 300 withdrawn, leaving the staple 302 in place to hold the leaflets together. Optionally, additional clips can be placed in a like manner to further strengthen  
25 the affixation of the leaflets. As described, the clip is a malleable clip which undergoes plastic deformation for emplacement. Alternatively, the clip could be formed of an elastic material, such as a shape memory alloy, and held in its open position as shown in  
30 Fig. 61A. The clip could then be placed by releasing it to return to its memory (closed) configuration, as shown in Fig. 61B. Other actuation mechanisms could also be used,  
20 such as the use of heat to induce a shape change in a heat memory alloy staple.

In addition, two part snaps, rivets and staples may be used to hold leaflets  
35 in place by locking together. This may be achieved by a number of device designs. Preferred embodiments involve two disks 850, pledgets, or the like, placed on opposite sides of tissues or leaflets LF to be bound together, as shown in Fig. 62A. Typically a  
25 shaft 852, pin or needle may pierce the leaflets LF and connect the two disks 850. The disks 850 may then be snapped or joined together by interlocking one or both disks 850 to the shaft 852 and/or portions of the shaft 852 to each other. Such a fixation device may  
40 be introduced through a lumen of a specialized catheter 854, introducer or component of an interventional tool, as shown in Fig. 62B. The disks 850 may be solid and/or rigid  
45 requiring placement on each side of the tissue, or the disks 850 may be flexible, collapsible and/or inflatable such that they may be inserted through the tissue for placement on the other side of the tissue. Preferred embodiments also involve two disks  
50 855, pledgets, or the like, which are placed between tissues or leaflets LF to be bound together, as shown in Fig. 62C. Here, the disks 855 have penetrating prongs 856 at each

5 end to pierce and grasp tissue. When the disks 855 are snapped or joined together by interlocking one or both disks 855 to a shaft 858, shown in Fig. 62D, and/or portions of the shaft 858 to each other, the leaflets LF may be bound together.

10 An additional embodiment of a two part rivet-like stapling mechanism is illustrated in Fig. 63. A stapling mechanism 322 at the distal end of a catheter 320 comprises a first jaw 324 which carries a fastener 326 and a second jaw 328 which carries a retaining ring 330. The fastener has a collapsible cone 332 at its distal end so that it may be forced into an aperture 334 in the retaining ring 330. The jaws 324 and 328 are pivotally mounted within the distal end 340 of the catheter so that they may be opened and closed to grasp the free ends of the valve leaflets therebetween. The closing of the jaws 324 and 328, however, does not lock the fastener 326 into the retaining ring 330. Thus, the valve leaflets can be temporarily grasped and the improvement in valve regurgitation visually assessed. If the improvement is sufficient, the fastener 332 can be driven into the tissue and locked in the retaining ring 330. If the improvement is not sufficient, the jaws can be repositioned on the valve leaflets one or more additional times until an adequate or optimized repositioning of the leaflets is obtained. The fastener 332 can be driven into the retaining ring in a variety of ways. In the illustrated embodiment, a cam device 342 is slidably mounted behind an inclined surface 344 on the rear of the fastener 326. By drawing the cam actuator 342 downwardly using draw cord 348, the rivet can be driven through the valve leaflets and into the retaining ring 330, as illustrated in Fig. 64.

35 In addition to rivets, snaps, pins and the like, coils may be used in a similar manner to fix valve leaflets in a desirable arrangement, as shown in Fig. 65A. Coils 900 may be comprised of a superelastic material and pre-shaped in a coil configuration for engagement with the leaflets. The coil 900 may be advanced from an introducer sheath 902 to deploy the coil 900 in an orientation that will approximate the leaflets in compression. Alternatively, the coil 900 may be comprised of a heat or current activated shape memory material. As depicted in Fig. 65B, the coil 900 may be straightened in its initial configuration for ease of piercing and advancing through the leaflets LF. When positioned, the material may be activated by heat or current to assume a shape memory coil configuration corresponding with Fig. 65A. Again, the coils may be oriented to approximate the leaflets in compression. To achieve maximum leaflet compression at the coaptation points, a super elastic or shape memory coil 900 may be delivered in a manner that places the coil in an inverted orientation across the leaflets, as illustrated in Fig. 65C.

5 This may be accomplished with the use of a specialized delivery system 904. When released from the delivery system 904, the distal end 905 of the coil produces a compressive force as the coil attempts to achieve a non-inverted orientation.

10 As a further alternative, a cinch-type fastener 360 may be positioned in a  
5 loop through opposed valve leaflets LF, as shown in Fig. 66. The fastener 360 could be advanced from either a retrograde or antegrade direction, but the antegrade direction is illustrated for convenience. A positioning catheter 362 can be introduced through a guide catheter 14 which has been previously positioned by any of the techniques described  
15 above. After advancing the cinch-type fastener 360 through the leaflets, for example by  
10 pushing a pre-shaped fastener 360 through the leaflets so that it returns to the distal tip of the placement catheter 360, a fastening collar 364 may then be advanced to tighten the fastener loop 360 until the leaflets are positioned in a desired fashion. Alternatively, the fastener 360 may be twisted to constrict the open loop. Typically, the fastener 360 has chevrons or other one-way surface features so that the locking column may be advanced  
20 and will remain in place without loosening over time, or in the case of twisting, untwisting over time. The fastener 360 is then released and, if desired, additional fasteners positioned in a like manner. The fastening collar 364 may alternatively be used to secure the sutures shown previously in Fig. 49. The collar 364 may be crimped onto the sutures 202 or locked in place by the use of a combination of one-way surface features  
25 on the collar 364 and sutures 202.

35 Further, a variety of penetrating and non-penetrating clips, barbs, grappling hooks, and the like, may be used to fasten valve leaflets in a desired configuration. As previously described as a means to grasp the free ends of the valve leaflets in a pinching manner, a pair of flat coils may also be used as a fixation device.  
25 As previously shown and described in relation to Fig. 46A, the coils 770 may be linked together with opposing curvature by a clip 772. When inserted as shown in Fig. 46B, the coils 770 may be permanently joined in this orientation and may remain as a permanent implant. Alternatively, the coils 910 may pierce the leaflets LF to hold them in place as shown in Figs. 66A and 66B. During placement, the coil 910 may be inserted through a  
40 delivery catheter 911 in a straight configuration and pierce the leaflets LF in this form, allowing the free distal end 912 of the coil 910 to curl after it has penetrated the leaflets LF, as shown in Fig. 66A. The proximal end may then curl after it disengages from the delivery catheter 911 to remain as an implant as shown in Fig. 66B.  
45  
50

5 Likewise, a variety of barb-like structures may be used in a similar fashion  
to fasten valve leaflets in a desired configuration. Referring to Fig. 67, a shaft 920 with  
one or several curved barb-like distal ends 922 may be positioned so that the distal ends  
10 partially or fully penetrate each leaflet LF to be fixed. The shaft 920 may be a shape  
5 memory or super elastic wire. By activating the shaft 920 with heat or current, in the case  
of a shape memory material, or allowing the shaft 920 to assume its pre-configured shape,  
in the case of a super elastic material, several barbs 922 may be approximated to coapt the  
15 leaflets in the desired position. On the other hand, several discontinuous barbs 922 may  
be tensioned and coapted using a crimping or coupling and trimming system. Similarly,  
10 as shown in Fig. 68, a shaft 924 with expanding barb-like distal ends 926 may be  
positioned so that the distal ends 926 penetrate each leaflet LF to be fixed. Here,  
20 however, the distal ends 926 may be comprised of one or more struts 927 which expand  
to further prevent retraction of the shaft 924. Such expansion may be achieved by  
activation of the shaft 924 with heat or current or allowing the device to assume its pre-  
25 configured shape. In addition to end 926 expansion, the shaft 924 may be approximated  
to coapt the leaflets or several discontinuous shafts may be tensioned and coapted using a  
crimping or coupling and trimming system.

30 In addition to fixation, clips may be used to draw leaflets together in a  
suitable coaptation configuration. While temporarily holding two or more leaflets in a  
20 desired configuration, such as with grasping tools, a clip may be deployed to maintain the  
desired position or to further manipulate the leaflets. For example, a clip 940 may be  
35 mounted on a delivery catheter or interventional tool 942, as shown in Fig. 69A. It may  
then be positioned in a desired location to hold the leaflets LF, as shown in Fig. 69B. In  
the deployed and activated state, depicted in Fig. 69C, the clip 940 may tend to pinch  
25 inwardly, pulling the leaflets together, as indicated by arrows 944. This may be achieved  
40 by activation of super elastic or shape memory material. Alternatively, referring to Figs.  
70A and 70B, the clip 945 may pinch inwardly, indicated by arrows 944, by manual  
crimping of the spine 946 or interlocking of the piercing legs 948. When positioned  
appropriately between the valve leaflets LF, as shown in Fig. 70B, the leaflets may be  
45 30 drawn together by crimping the spine 946 of the clip 945 with the use of a removable  
actuator 950. As the actuator 950 passes over the spine 946, the spine 946 may be  
plastically deformed to a new configuration. Or, as the actuator 950 passes over the spine  
50 946, the proximal ends of the piercing legs 948 may become interlocked. In either case,  
inward movement of the clip 945 may be controlled by passing the actuator 950 only over

5 portions of the spine 946 in which such pinching is desired. Therefore, a single clip may provide variable inward forces.

10 Inward forces may also be applied by components of an interventional tool, such as a by graspers. Graspers, as previously described, are devices which grasp  
5 and hold tissues (such as coapting valve leaflets) for appropriate modification, such as fixation. Thus, graspers are most likely in place while a fixation device is deployed and positioned. Referring to Fig. 71, an embodiment of graspers 960 is shown holding the  
15 leaflets LF on opposite sides of a deployed clip 962. Inward force may be applied to the clip 962 by moving or applying force to the graspers 960 in an inward direction, as depicted by arrows. In a further embodiment, the graspers may serve as a grasping device  
20 and as an implantable fixation device. Referring to Fig. 72A, an embodiment of graspers 960 is shown coapting and holding the leaflets LF together. The graspers 960 may then be joined by a coupling device 964 and detached for implantation, as shown in Fig. 72B.

25 Because of the fragility of the tissue in the valve leaflets, it will sometimes be preferred to utilize methods or devices which do not completely pierce or penetrate the tissue. For example, leaflets may be fused together in a desired coaptation position by  
30 applying laser, RF, microwave or ultrasonic energy at specified coaptation points. In addition or alternatively, external clips which are partially penetrating or non-penetrating may be used. A variety of deformable and elastic clips can be utilized, and clips will  
20 usually be deployed in a retrograde fashion so that an opening in the clip can be placed over the undersides of the adjacent valve leaflets.

35 A preferred clip-applying catheter 380 in is depicted in Figs. 73A, 73B, and 73C. The catheter 380 has a three-jaw clip-applying device 382 at its distal end. The three-jaw structure allows the clip-applier to be used as a three-jaw grasping device  
25 before final deployment of the clip. Such grasping has been described earlier with reference to Figs. 42A, 42B, and 43 above. A center jaw 384 of the device has a tubular structure and allows the catheter to be introduced over a guidewire 386, where the  
40 guidewire may be placed through the atrioventricular valve prior to catheter positioning. A clip 388 has a V-shaped structure and is normally closed so that a force is required to  
45 open the distal ends of the clip. Jaws 390 and 392 hold the clip and can open the clip by selectively opening either jaw, with jaw 392 shown in open in broken line in Fig. 73A.  
30 Thus, jaw 392 may be opened first to capture a free end of a first valve leaflet. With the catheter 380 thus attached to just the first valve leaflet, the catheter can be repositioned so  
50 that the other jaw 390 can be opened and used to capture the second valve leaflet. After

the valve leaflets are captured and held in a proper orientation, valve improvement can be confirmed by visual observation. If improvement is sufficient, the clip can be detached from the catheter and left in place, as shown in Fig. 74.

B. Shortening of the Chordae

In addition to suturing, fastening, and otherwise physically attaching portions of the valve leaflets and/or chordae together, valve leaflet closure can be improved by shrinking portions of either or both of the chordae attached to the two valve leaflets. An exemplary catheter 400 having an energy-applying coil 402 at its distal end is shown in Fig. 75. Such energy may be in the form of radiofrequency (RF), microwave, ultrasound, laser, heat or current. The catheter 400 may be deployed in either an antegrade or retrograde direction, with retrograde generally being preferred to facilitate access to the chordae. One or more chordae CT are captured within the coil and RF energy, for example, applied from a conventional power supply. Application of the RF energy to the chordae, which are composed of collagen and other normal tissue constituents, over a length L will cause shrinkage of the tissue to a length which is shorter than the original length L. Similarly, such application of energy to the chordae may also be achieved with the use of an energy applying chordal snare or similar device. By applying such shortening of the chordae, valve conditions, such as prolapsed valves can be effectively treated.

In addition to the use of energy for shortening chordae, the chordae can be plicated using mechanical plication devices 420, as illustrated in Fig. 76. Each of the devices 420 comprise a cap piece 422 and a receptacle 424. A receptacle has a channel 426 which receives a pin 428 on the cap piece 422. There is sufficient clearance between the pin 428 and channel 426 so that a portion of the chordae CT can be captured and folded therein by placing the cap into the receptacle. Each plication device 420 will thus shorten a portion of the chordae by a predetermined amount. Multiple devices can be used to achieve a desired overall shortening of the chordae. The devices can be placed using jaw-type devices and shortening can be visually observed by any of the techniques described above. Alternatively, chordae may be mechanically plicated with the use of suture loops. Referring to Fig. 77A, a suture 980 may penetrate the chordae CT at a first location 982 and then penetrate the chordae CT again at a second location 984 forming a loop. By pulling closed the loop, as shown in Fig. 77B, the effective length of the chordae CT is reduced. The suture loop may then be fixed and trimmed for implantation. This may be repeated along a chordae to form multiple individual or continuous loops,



5 and/or it may be repeated on along more than one chordae. Similarly, such plication may also be achieved with the use of a shape memory or super elastic wire coil which may penetrate a chordae at one or more points and draw the tissue together upon activation.

10 C. Annuloplasty

5 The intravascular approaches of the present invention, particularly the antegrade approaches, can also be used to place supporting rings and devices around the atrioventricular valve annulus. Such devices can provide support which is analogous to that provided by annuloplasty rings implanted in open surgical procedures. In one approach, an elastic annuloplasty ring can be delivered through the guide catheter in a collapsed fashion, deployed to open over the annulus, and then stitched or stapled in place using appropriate catheters.

20 A first exemplary annuloplasty ring 500 can be deployed using a catheter 502 positioned through a guide catheter 14, as generally shown in Fig. 78. The annuloplasty ring 500 is deployed as an umbrella having spokes 504 which open the outer ring. After deploying the ring, it may be secured in place using sutures, staples, tissue adhesives, or other conventional techniques. The catheter 502 may then be removed, together with the deployment spokes 504, leaving the ring permanently in place.

30 Alternatively, an annuloplasty ring 520 can be delivered on a balloon catheter 522 as shown in Figs. 79 and 80. The ring 520 can be formed from a deformable material, and the balloon 520 inflated within the valve annulus to expand and deploy the ring, as shown in Fig. 80. The balloon catheter may be placed directly over a guidewire 524, but will more usually be positioned using a combination of a guide catheter and guidewire. Once the ring 520 is deployed, it can be sutured, stapled, glued, or otherwise affixed around the valve annulus.

35 40 45 50 As an alternative to placement of discrete annuloplasty rings, the valve annulus can be reinforced and tightened by placing a plurality of anchors, such as staples 540 about the annulus of the mitral valve, as shown in Fig. 81. A suture 542 or other filament can then be placed through the anchors 540 and tightened in a "purse string" fashion. The suture filament can then be tied off to maintain the desired tightening and enforcement of the valve annulus.

55 As yet a further alternative, the valve annulus can be plicated by positioning a plurality of staples about the annulus, as shown in Fig. 82. Here, each staple 560 plicates or shortens a small peripheral segment of the annulus. A staple applying

5 catheter 562 may have the same general structures described above in connection with Figs. 61A and 61B.

10 X. DEVICE EMBODIMENTS

The following three device embodiments depict complete device designs  
5 utilizing a variety of the specific components described above and/or new component designs to accomplish similar objectives.

15 A. Atrial Device

Referring to Fig. 83, the atrial device 1000 is comprised of a catheter shaft  
1002 having a distal end 1004 and a proximal end 1006. The catheter shaft 1002 is  
20 comprised of, among others, a conduit 1008, a coaxial outer sheath 1010, and a central guidewire lumen 1011. Toward the distal end 1004, a pair of stabilizers 1012 having a single-hump shape (previously illustrated in Fig. 31D) are fixedly mounted on the outer sheath 1010 at their proximal end 1014 and fixedly attached or hinged to extenders 1016 at their distal end 1018. The stabilizers 1012 are shown in an outwardly bowed position,  
25 however they may be inwardly collapsed by either extending the extenders 1016 or retracting the outer sheath 1010. Bowing may be achieved by the reverse process.

Referring to Fig. 84, the atrial device 1000 may be used with a typical  
30 antegrade approach to the mitral valve MV. As previously described and depicted in Figs. 7 and 8, such an antegrade approach may involve penetrating the interatrial septum IAS and maintaining such access with a guide catheter 14. The guide catheter 14 permits  
20 introduction of the atrial device 1000 to the left atrium LA and mitral valve MV. To allow passage of the device 1000 through the guide catheter 14, the stabilizers 1012 must be in a collapsed position as shown. In addition, graspers, described below, may be fully retracted to avoid damage to cardiac structures. Thus, they are not visible in Fig. 84.

Referring to Fig. 85, the atrial device 1000 may be stabilized against the  
40 mitral valve MV. The stabilizers 1012 may be inserted through the mitral valve MV and may be aligned with the line of coaptation C between the valve leaflets LF1, LF2. To minimize mitral valve regurgitation (MVR) due to insertion of the device 1000, the stabilizers 1012 may be located approximately 120 degrees apart. This angle may be  
45 fixed or adjustably variable. The single-humped shape of the stabilizers 1012 may allow the inferior portion 1030 to pass within the valve and apply radial pressure to the commissures CM and the superior portion 1032 (or hump) to rest upon and apply axial  
30 pressure to the commissures CM.

5 Referring again to Fig. 83, a pair of graspers, comprised of grasping  
sheaths 1020 and three opposing prongs 1021 configured to partially or fully penetrate or  
pierce, are shown extended from the conduit 1008 in the plane bisecting the angle of the  
10 stabilizers 1012 (i.e. approaches the middle of the leaflets). This angle may be fixed or  
5 variable. When not in use, however, the graspers may be fully retracted within the  
conduit 1008. Tension from lateral steering wires 1022 cause the graspers to deflect  
away from each other and approximate the most desirable angle for grasping. Amount of  
15 deflection may be controlled from the proximal end of the device by the steering wires  
1022. When the graspers are positioned in a desired location as shown in Fig. 85, the  
10 prongs 1021 may be deployed and opened by either retraction of the grasping sheath 1020  
or advancement of the prongs 1021 beyond the grasping sheath 1020. Retraction of the  
20 sheath 1020 does not significantly affect the position of the graspers, thus enabling the  
user to contact the valve leaflets LF1, LF2 with the prongs 1021 housed within the sheath  
1020 and then to initiate grasping the leaflets at the contacted location by retracting the  
25 grasping sheaths 1020. The opposing prongs 1021 may be closed to grasp (pinch,  
partially penetrate or pierce) the leaflet tissue by advancing the grasping sheaths 1020 or  
retracting the prongs 1021 within the sheaths 1020.

30 After both leaflets have been grasped, tension in the steering wires 1022 is  
released and the conduit 1008 is advanced over the grasping sheaths 1020. Such  
20 advancement draws the sheaths 1020, and grasped leaflets, together for coaptation. After  
coaptation, the mitral valve regurgitation is evaluated to determine if the locations which  
are grasped are appropriate for fixation. If the grasping points are not appropriate, the  
35 leaflets may be released and regrasped individually or simultaneously by the above  
described methods. If the grasping points are appropriate, the preferred embodiment  
25 allows for exchange of the guidewire, located in the guidewire lumen 1011, for a fixation  
device. The fixation device may use, for example, staples, sutures, clips, rivets, coils,  
40 fusing devices, zippers, snares, clamps, hooks, chordal fixation or shortening devices to  
repair the mitral valve regurgitation. Specifically, the fixation device may be the hollow  
suturing coil 1300 shown previously in Figs. 49A-C. As shown in Fig. 84A, the hollow  
45 suturing coil 1300 containing suture 1302 (not shown) may be deployed through the  
guidewire lumen 1011 in a coiled configuration. The coil 1300 may expand or change  
shape once it is deployed from the lumen 1011, providing the coil 1300 is comprised of a  
50 suitable shape memory or superelastic material. Similarly, as shown in Fig. 84B, the  
suturing coil 1300 may be deployed through the guidewire lumen 1011 in a straightened

5 configuration such that it coils and/or expands or changes shape once it is deployed from the lumen 1011.

10 The above described components may be manipulated and controlled by a handle 1026 connected to the proximal end 1006 of the catheter shaft 1002, as shown in Fig. 83. The handle 1026 permits independent control of the components, including but not limited to retraction and extension of extenders 1016, deployment of stabilizers 1012, adjustment and locking of outer sheath 1010, translation and deflection of grasping sheaths 1020, stopping and locking of grasping sheaths 1020 and axial sliding of the conduit 1008. In addition, the device may be readily adapted to approach the mitral valve trans-atrially for a minimally invasive surgical (MIS) procedure, with either beating or stopped heart.

20 B. Atrial-Ventricular Device

Referring to Fig. 86, the atrial-ventricular device 1100 is comprised of a catheter shaft 1102 having a distal end 1104 and a proximal end 1106. The catheter shaft 1102 is comprised of, among others, a conduit 1108, a coaxial outer sheath 1110, a central lumen 1111 through which a double-jaw grasper 1113 may be inserted, and a central guidewire lumen 1105. Toward the distal end 1104, a pair of stabilizers 1112 having a triangular shape (previously illustrated in Fig. 31A) are fixedly mounted on the outer sheath 1110 at their proximal end 1114 and fixedly attached to extenders 1116 at their distal end 1118. The stabilizers 1112 are shown in an outwardly bowed position, however they may be inwardly collapsed by either extending the extenders 1116 or retracting the outer sheath 1110. Bowing may be achieved by the reverse process. The double-jaw grasper 1113 is comprised of two articulating jaw arms 1120 which may be opened and closed against the central shaft 1122 (movement depicted by arrows) either independently or in tandem. The grasper 1113 is shown in the open position in Fig. 86. The surfaces of the jaw arms 1120 and central shaft 1122 may be toothed, as shown, or may have differing surface textures for varying degrees of friction.

Referring to Figs. 87A-C, the atrial-ventricular device 1100 may be used with a typical antegrade approach to the mitral valve MV, as previously described and depicted in Figs. 7 and 8. However, the double-jaw grasper 1113 extends through the valve such that the leaflets L1, L2 are grasped from below. Thus, the device 1100 is termed "atrial-ventricular."

Referring to Fig. 87A, the atrial device 1100 may be stabilized against the mitral valve MV. The stabilizers 1112 may be positioned on the superior surface of the

5 valve leaflets LF1, LF2 at a 90 degree angle to the line of coaptation. The grasper 1113  
may be advanced in its closed position from the conduit 1108 between the leaflets LF1,  
10 LF2 until the jaw arms 1120 are fully below the leaflets in the ventricle. At this point, the  
grasper 1113 may be opened and retracted so that the jaw arms 1120 engage the inferior  
5 surface of the leaflets LF1, LF2. In this manner, the leaflets are secured between the  
stabilizers 1112 and the jaw arms 1120. This action allows for leaflets of many different  
shapes and orientations to be secured. Cardiomyopathic valves are often enlarged and  
15 distorted so that they coapt irregularly. Such irregularity creates difficulty in  
mechanically coapting such valves for tissue modification. The action of the grasper  
10 1113 overcomes much of these difficulties.

Referring to Fig. 87B, the grasper 1113 will gradually close, drawing the  
20 leaflets LF1, LF2 together while maintaining a secure hold on the leaflets between the  
jaw arms 1120 and the stabilizers 1112. This may be accomplished by number of  
methods. For example, the stabilizers 1112 may be gradually collapsed by either  
25 extending the extenders 1116 or retracting the outer sheath 1110. As the stabilizers 1112  
collapse, the jaw arms 1120 may collapse due to spring loading to gradually close the  
grasper 1113. Alternatively, the jaw arms 1120 may be actuated to close against the  
central shaft 1122 applying force to the stabilizers 1112 causing them to collapse. In  
30 either case, such action allows the stabilizers 1112 to simultaneously vertically retract and  
withdraw from the leaflets as the leaflets are clamped between the jaw arms 1120 and the  
20 central shaft 1122. In this manner, the leaflets are effectively "transferred" to the grasper  
1113. Referring to Fig. 87C, once the collapsed stabilizers 1112 are completely  
35 withdrawn, the leaflets LF1, LF2 are held in vertical opposition by the grasper 1113 in a  
more natural coaptation geometry. At this point the leaflets may be adjusted and fixated.  
25 Fixation may be achieved with an external element or the grasper 1113 may be left in  
place as a fixation device.

The above described components may be manipulated and controlled by a  
40 handle 1126 connected to the proximal end 1106 of the catheter shaft 1102, as shown in  
Fig. 86. The handle 1026 permits independent control of the components described  
45 30 above.

#### C. Ventricular Device

Referring to Fig. 88, the ventricular device 1200 is comprised of a catheter  
50 shaft 1202 having a distal end 1204 and a proximal end 1206. The distal end 1204 is  
comprised of a joining coil 1208, an upper jaw 1210, a lower jaw 1212, an actuator 1214

5 and a central lumen 1216 through which a guidewire 1218 or other wires may be inserted. The upper jaw 1210 may open and close (depicted by arrows) against the lower jaw 1212 by action of the actuator 1214. The upper jaw 1210 is shown in the open position. These components may be manipulated and controlled by a handle 1226 connected to the proximal end 1206 of the catheter shaft 1202 as shown.

Referring to Figs. 89, the ventricular device 1200 may be used with a typical retrograde approach to the mitral valve MV, as previously described and depicted in Fig. 9. Here the mitral valve MV may be accessed by an approach from the aortic arch AA across the aortic valve AV, and into the left ventricle LV below the mitral valve MV. Such access may be maintained with a guide catheter 40 through which the ventricular device 1200 may be introduced. The ventricular device 1200 may be inserted through the guide catheter 40 with the upper jaw 1210 in the closed position. After it exits the guide catheter 40 just below the aortic valve AV, the device 1200 may be advanced toward the mitral valve MV. The catheter shaft 1202 may be pre-shaped to provide favorable curvature in positioning the distal end 1204 beneath the valve leaflets ALF, PLF. Additionally, two mandrels with favorable shapes may be advanced into a lumen in the catheter shaft 1202. By changing the location of the mandrels with respect to each other and to the catheter shaft 1202, the general curvature of the shaft 1202 may be altered in-situ.

It is desired to position the distal end 1204 of the device 1200 beneath the mitral valve leaflets ALF, PLF with the upper jaw 1210 in the open configuration. The lower jaw 1212 is to be proximal to the anterior leaflet ALF and the upper jaw 1210 is to be distal of the posterior leaflet PLF, as shown in Fig. 89, such that the leaflets may be secured between the jaws 1210, 1212. To achieve such positioning, the device 1200 may be required to flex at an extreme angle in the region of the joining coil 1208. Therefore, the joining coil 1208 is designed to provide such flexibility.

To aid in positioning the device 1200, a balloon wire 1250 may be used. The balloon wire 1250 may first be inserted through the aortic valve AV, advanced down to the apex of the ventricle and then back upwards towards the mitral valve MV behind the posterior leaflet PLF. Once positioned, the balloon 1252 may be inflated to assist in holding the position stationary. A cuff wire 1260 may then be inserted through the aortic valve AV. The cuff wire 1260 may track along the balloon wire 1250 by means of a locking ring 1262. The cuff wire 1260 may track down to the apex of the ventricle and then back upwards toward the mitral valve MV. Once the cuff wire 1260 is advanced to a

5 desirable position, the locking ring 1262 may be actuated to lock the cuff wire 1260 to the  
balloon wire 1250. A typical means of actuation is by inflation of the locking ring. 1262.  
The ventricular device 1200 may then be tracked over the cuff wire 1260 to the desired  
10 position, as shown in Fig. 89. The balloon, or balloon wire 1250, may also be used to  
5 walk or urge the posterior leaflet towards the center of the valve to facilitate grasping.

Once positioned, the upper jaw 1210 may be closed against the lower jaw  
1212 such that the leaflets are grasped between them. It is often desirable to adjust or  
15 manipulate the leaflets once they are grasped. Manipulation should occur only in a  
superior/inferior (up/down) motion in order to bring the leaflets to a final position where  
10 regurgitation is minimized. The lower jaw 1212 may be fitted with a travel mechanism  
for extending or retracting the jaw 1212. This would move one leaflet up or down with  
20 respect to the other leaflet. Once the leaflets are sufficiently adjusted, fixation may occur  
in any manner previously described. In a preferred embodiment, fixation may be achieved  
through the lower jaw 1212, as depicted in Figs. 90A and 90B. As shown in Fig. 90A, a  
25 cutout 1270 may be present in the lower jaw 1212 accessing a lumen 1272 which extends  
through the catheter shaft 1202 and lower jaw 1212; such a lumen may also serve as the  
guidewire lumen 1216. When the upper jaw 1210 is closed against the lower jaw 1212,  
30 the valve leaflets LF may be captured between the jaws. As shown a side-view, Fig. 90B,  
the captured leaflets LF may protrude into through the cutout 1270 into the lumen 1272.  
20 A fixation device 1274 may then be inserted through the lumen 1272 (in the direction of  
the arrow) and may affix the leaflets LF together. It may be appreciated that such a  
method of fixation may be used in a number of devices involving jaw-type graspers, such  
35 as the atrial ventricular device 1100 depicted in Fig. 86.

Although the foregoing invention has been described in some detail by way  
25 of illustration and example, for purposes of clarity of understanding, it will be obvious  
40 that various alternatives, modifications and equivalents may be used and the above  
description should not be taken as limiting in scope of the invention which is defined by  
the appended claims.

**Claims**

5

10

15

20

25

30

35

40

45

50

55



5

WHAT IS CLAIMED IS:

10

15

20

25

30

35

40

45

50

55

1. A method for repairing an atrioventricular valve, said method comprising:
- accessing a patient's vasculature remote from the heart;
- advancing an interventional tool through the vasculature to a ventricle; and
- engaging the tool against a tissue structure which forms or supports the atrioventricular valve, wherein the tool modifies the tissue structure in a manner that reduces leakage through the valve during ventricular systole.
2. A method as in claim 1, further comprising orienting the interventional tool relative to the atrioventricular valve or tissue structure prior to engaging the tool against the tissue structure.
3. A method as in claim 2, wherein orienting comprises positioning the tool relative to a line of coaptation in the atrioventricular valve.
4. A method as claim 3, wherein positioning comprises engaging positioning elements in the valve commissures.
5. A method as in claim 1, wherein the tissue structure is selected from the group consisting of valve leaflets, chordae, the valve annulus, and papillary muscles.
6. A method as in claim 1, wherein the tissue structure comprises the valve leaflets and the engaging step comprises attaching opposed points on or along the valve leaflets together.
7. A method as in claim 6, wherein attaching comprises suturing, clipping, stapling, riveting, gluing, or fusing said opposed points together.
8. A method as in claim 6, wherein the opposed points are located from 1 mm to 4 mm inward from the free edge of the valve leaflet.
9. A method as in claim 6, wherein engaging the interventional tool comprises:
- capturing the valve leaflets; and

- 5 4 holding the leaflets together at one or more adjacent points.
- 1 10. A method as in claim 9, further comprising observing flow through  
2 the held valve leaflets to determine if regurgitation has been inhibited.
- 10 1 11. A method as in claim 10, further comprising securing the leaflets  
2 together at said adjacent point(s) if regurgitation has been sufficiently inhibited.
- 15 1 12. A method as in claim 10, further comprising repositioning the held  
2 valve leaflets if the regurgitation has not been sufficiently inhibited.
- 20 1 13. A method as in claim 1, wherein the tissue structure comprises the  
2 chordae and the engaging step comprises linking opposed chordae together.
- 1 14. A method as in claim 13, wherein linking comprises suturing,  
2 capturing, fusing, or gluing the opposed chordae.
- 25 1 15. A method as in claim 1, wherein the tissue structure comprises the  
2 chordae and the engaging step comprises shortening the chordae.
- 30 1 16. A method as in claim 15, wherein the shortening step comprises  
2 applying radiofrequency energy to portions of the chordae.
- 1 17. A method as in claim 15, wherein the shortening step comprises  
2 mechanically plicating the chordae.
- 35 1 18. A method as in claim 1, wherein the tissue structure comprises the  
2 valve annulus and the engaging step comprises circumferentially tightening the annulus.
- 40 1 19. A method as in claim 18, wherein circumferentially tightening the  
2 annulus comprises positioning and attaching a supporting structure to the annulus.
- 1 20. A method as in claim 18, wherein circumferentially tightening  
2 comprises plicating the annulus.
- 45 1 21. A method as in claim 18, wherein circumferentially tightening  
2 comprises applying energy to shrink at least a portion of the annulus.

50

55

5

1 22. A method as in claim 1, wherein the tissue structure comprises  
2 papillary muscles and the engaging step comprises capturing and drawing opposed points  
3 of the papillary muscles together.

10

1 23. A method as in claim 22, wherein capturing and drawing comprises  
2 attaching the opposed points partially together.

15

1 24. A method as in claim 1, wherein the heart remains beating while  
2 the interventional tool is engaged against the tissue structure.

20

1 25. A method as in claim 1, further comprising stopping the heart  
2 while the tool is engaged against the tissue structure.

25

1 26. A method as in claim 25, wherein the heart is temporarily stopped  
2 by drug injection.

30

1 27. A method as in claim 25, wherein the patient is on  
2 cardiopulmonary bypass.

1 28. A method as in claim 1, wherein valve action is stopped  
2 temporarily.

35

1 29. A method as in claim 28, wherein valve action is stopped by  
2 raising the pressure in the ventricle above pressure in the atrium during diastole.

40

1 30. A method as in claim 28, wherein valve action is stopped by drug  
2 administration.

1 31. A method as in claim 28, wherein valve action is stopped by  
2 mechanically restraining the leaflets.

45

1 32. A method as in claim 24, further comprising stabilizing the  
2 interventional tool relative to valve leaflets prior to engaging the leaflets with the  
3 interventional tool.

50

1 33. A method as in claim 32, wherein stabilizing comprises releasably  
2 capturing chordae attached to each leaflet.

55

5

1 34. A method as in claim 33, wherein releasably capturing the chordae  
2 comprises advancing a snare through the network of chordae and tightening the snare.

10

1 35. A method as in claim 32, wherein stabilizing comprises releasably  
2 grasping each leaflet.

15

1 36. A method as in claim 32, wherein stabilizing comprises releasably  
2 coupling the interventional tool to a tissue structure.

20

1 37. A method as in claim 36, wherein the tissue structure is selected  
2 from the group consisting of the interatrial septum, the atrial wall, the valve annulus, the  
3 chordae, the papillary muscles, and the commissures.

25

1 38. A method as in claim 32, wherein stabilizing comprises  
2 mechanically fixing the shape of the interventional tool after the tool has been advanced  
3 to the valve.

30

1 39. A method as in claim 1, wherein accessing comprises accessing a  
2 vena cava and advancing comprises passing the interventional tool into the right atrium,  
3 passing the tool through the interatrial septum into the left atrium, and approaching the  
4 mitral valve from above.

35

1 40. A method as in claim 39, wherein accessing further comprises  
2 entering the venous vasculature through an access location in the inferior vena cava, the  
3 superior vena cava, a femoral vein, or an internal jugular vein, and advancing the  
4 interventional tool from the access location into the right atrium.

40

1 41. A method as in claim 40, wherein entering, the venous vasculature  
2 comprises introducing the interventional tool percutaneously into a femoral artery,  
3 advancing the interventional tool upwardly through the inferior vena cava into the right  
4 atrium, forming a passage through the interatrial septum into the left atrium, advancing  
5 the interventional tool through the passage into the left atrium, and turning the tool  
6 downward to direct a working end thereof at the mitral valve.

45

50

1 42. A method as in claim 41, wherein forming the passage comprises  
2 penetrating a needle through the atrial septum.

55

5

1 43. A method as in claim 41, wherein turning the tool downward  
2 comprises everting a distal tip of the tool.

10

1 44. A method as in claim 40, wherein entering comprises  
2 percutaneously entering the access location with a sheath.

15

1 45. A method as in claim 40, wherein entering comprises surgically  
2 opening a passage to the access location in the arterial vasculature.

20

1 46. A method as in claim 40, wherein accessing further comprises  
2 placing a guide catheter from the access location to the right atrium, through the  
3 interatrial septum, and into the left atrium, wherein the interventional tool is passed  
4 through the guide catheter.

25

1 47. A method as in claim 46, further comprising coupling the guide  
2 catheter to the integrated septum to stabilize the guide catheter.

30

1 48. A method as in claim 47, wherein coupling comprises inflating a  
2 pair of balloons on the guide catheter to capture the septum therebetween.

35

1 49. A method as in claim 46, wherein accessing further comprises  
2 engaging a distal structure on the guide catheter against the mitral valve, tissue  
3 surrounding the mitral valve, or an internal surface of the left atrium.

40

1 50. A method as in claim 49, wherein stabilizing elements coupled to  
2 the guide catheter are engaged against the mitral valve annulus.

1 51. A method as in claim 49, wherein stabilizing elements coupled to  
2 the guide catheter are engaged against the commissures of the mitral valve.

45

1 52. A method as in claim 40, wherein accessing further comprises  
2 engaging a distal structure on the interventional tool against the mitral valve, tissue  
3 surrounding the mitral valve, or an internal surface of the left atrium.

50

1 53. A method as in claim 1, wherein accessing comprises accessing the  
2 aortic arch and advancing comprises passing the interventional tool through the aortic  
3 valve into the left ventricle and approaching the mitral valve from below.

55

5

1                   54. A method as in claim 53, wherein accessing further comprises  
2 entering the arterial vasculature through an access location in the femoral artery, the  
3 brachial artery, or a carotid artery and advancing the interventional tool from the access  
4 location to the aortic arch.

10

1                   55. A method as in claim 54, wherein entering comprises  
2 percutaneously entering the access location with a sheath.

15

1                   56. A method as in claim 54, wherein entering comprises surgically  
2 opening a passage to the access location in the arterial vasculature.

20

1                   57. A method as in claim 53, wherein accessing further comprises  
2 placing a guide catheter from the access location through the aortic valve into the left  
3 ventricle, wherein the interventional tool is advanced through the guide catheter.

25

1                   58. A method as in claim 57, wherein accessing further comprises  
2 engaging a distal structure of the guide catheter against the mitral valve, the mitral valve  
3 chordae, the papillary muscles, or an internal surface of the left ventricle.

30

1                   59. A method as in claim 58, wherein stabilizing elements coupled to  
2 the guide catheter are engaged against the commissures, or the annulus of the mitral  
3 valve.

35

1                   60. A method as in claim 58, wherein stabilizing elements coupled to  
2 the guide catheter are engaged against the internal surface of the left ventricle.

40

1                   61. A method as in claim 58, wherein the stabilizing elements are  
2 balloons and the engaging step comprises inflating the balloons against the internal  
3 structure of the left ventricle.

45

1                   62. A method as in claim 58, wherein the stabilizing elements are wire  
2 or cage structures and the engaging step comprises deploying the wire or cage structures  
3 laterally against the internal surface of the left ventricle.

50

1                   63. A method as in claim 1, further comprising visualizing the mitral  
2 valve and surrounding tissue structures during engaging and modifying the tissue  
3 structure.

55

5

1 64. A method as in claim 63, wherein visualization comprises trans-  
2 esophageal echocardiography, fluoroscopy, or angioscopy.

10

1 65. A system for repairing a cardiac valve, said system comprising:  
2 a guidecatheter configured to pass from the remote vasculature of a patient  
3 to a position within the heart adjacent to the cardiac valve;  
4 an interventional catheter configured to pass through the guide catheter to  
5 engage the cardiac valve, the valve annulus, the papillary muscles, or the valve chordae;  
6 and  
7 an interventional tool on the interventional catheter adapted to modify the  
8 cardiac valve, the valve annulus, the papillary muscles, or the valve chordae to reduce  
9 regurgitation.

15

20

25

1 66. A system as in claim 65, wherein the guide catheter comprises a  
2 stabilizing mechanism for engaging a tissue structure within the heart to reduce relative  
3 movement between the guide catheter and the heart.

30

1 67. A system as in claim 66, wherein the stabilizing mechanism is  
2 adapted to engage at least one of the interatrial septum, the atrial wall, the valve annulus,  
3 and the valve commissures.

35

1 68. A system as in claim 66, wherein the stabilizing mechanism  
2 comprises an extensible wire that is deployed radially outward to engage the tissue  
3 structure.

40

1 69. A system as in claim 66, wherein the stabilizing mechanism  
2 comprises an expansible cage that occupies the atrium.

45

1 70. A system as in claim 66, wherein the stabilizing mechanism  
2 comprises a pair of spaced-apart inflatable balloons adapted to capture the interatrial  
3 septum therebetween.

50

1 71. A system as in claim 65, wherein the interventional catheter  
2 comprises a stabilizing mechanism for engaging a tissue structure within the heart to  
3 reduce relative motion between the interventional catheter and the heart.

55

5

1                   72. A system as in claim 71, wherein the interventional tool comprises  
2 a valve leaflet capture device for temporarily holding the valve leaflets prior to  
3 modification.

10

1                   73. A system as in claim 72, wherein the valve leaflet capture device  
2 comprises at least two jaws which grasp the valve leaflets.

15

1                   74. A system as in claim 72, wherein the valve leaflet capture device  
2 comprises at least one radially expansible superior loop and at least one radially  
3 expansible inferior loop, wherein the superior loop contacts a superior surface of the  
4 valve leaflet and the inferior loop contacts an inferior surface of the valve leaflet when the  
5 loops are in an expanded position to capture a portion of the valve leaflet between the  
6 loops.

20

1                   75. A system as in claim 72, wherein the valve leaflet capture device  
2 comprises a pair of opposing coils, wherein each coil curves outwardly and upwardly to  
3 contact an inferior surface of a valve leaflet and capture the valve leaflets between the  
4 coils.

25

1                   76. A system as in claim 72, wherein the valve leaflet capture device  
2 comprises at least two opposing prongs arranged to grasp a valve leaflet.

30

1                   77. A system as in claim 76, wherein the opposing prongs are opened  
2 by retraction of a grasping sheath and closed by advancement of the grasping sheath over  
3 at least a portion of the prongs.

35

1                   78. A system as in claim 72, wherein the valve leaflet capture device  
2 comprises a vacuum or suction applicator to capture the valve leaflet.

40

1                   79. A system as in claim 65, wherein the interventional tool is selected  
2 from the group consisting of suturing devices, stapling devices, clip-applying devices,  
3 radiofrequency electrodes, and annuloplasty ring-applying devices.

45

1                   80. A system as in claim 65, further comprising a chordae capture  
2 catheter for repair of an atrioventricular valve.

50

55



5

1 81. A method for stabilizing an atrioventricular valve, said method  
2 comprising:  
3 capturing chordae attached to at least one leaflet of the valve while the  
4 heart is beating.

10

1 82. A method as in claim 81, wherein capturing comprises capturing  
2 chordae attached to two valve leaflets.

15

1 83. A method as in claim 81, wherein capturing comprises advancing a  
2 snare to entangle the chordae.

20

1 84. A method as in claim 81, further comprising affixing the valve  
2 leaflets while the chordae remain captured.

25

1 85. A method as in claim 81, further comprising affixing chordae  
2 attached to two valve leaflets while the chordae remain captured.

30

1 86. A method as in claim 81, further comprising shortening the valve  
2 chordae while the chordae remain captured.

35

1 87. A chordae capture catheter comprising:  
2 a catheter body having a proximal end and a distal end;  
3 means at the distal end of the catheter for capturing chordae.

40

1 88. A catheter as in claim 87, wherein the capture means comprises a  
2 coil which is extensible from the distal end of the catheter body and which entangles the  
3 chordae when advanced therein.

45

1 89. A catheter as in claim 87, wherein the capture means comprises a  
2 loop element which is extensible from the distal end of the catheter body and which is  
3 preformed to pass through chordae and return to the catheter body to complete a loop.

50

1 90. A method for immobilizing two valve leaflets in a cardiac valve,  
2 said method comprising:  
3 providing a leaflet capture catheter having at least three grasping prongs;  
4 capturing a first valve leaflet between a first pair of prongs; and  
5 capturing a second valve leaflet between a second pair of prongs.

55

5

1                    91.    A method as in claim 90, wherein the two leaflet capture steps are  
2    performed sequentially.

10

1                    92.    A method as in claim 90, further comprising affixing the valve  
2    leaflets after they both are captured.

15

1                    93.    A valve leaflet capture catheter, said catheter comprising:  
2                    a catheter body having a proximal end and a distal end; and  
3                    a leaflet grasper at the distal end of the catheter body, said grasper  
4    including at least three prongs wherein at least two of the three are pivotable so that they  
5    may be separately actuated to separately capture individual leaflets.

20

1                    94.    A catheter as in claim 93, further comprising means for affixing the  
2    valve leaflets after they are captured.

25

1                    95.    A catheter as in claim 94, wherein the affixing means comprises a  
2    clip-applier or stapler.

30

35

40

45

50

55




FIG-1




FIG-2

3/84




FIG-3




FIG- 3A




FIG- 3B




FIG-4

FIG-5





FIG-6








FIG-7




FIG-3




FIG - 9




FIG-10






FIG - 11






FIG-13




FIG-14






FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG 16




FIG. 17




FIG. 18




FIG. 19




FIG 20




FIG 21A




FIG 21B




FIG 21C




FIG 22A




FIG 22B




FIG. 23




FIG- 24



23/84




FIG 25




FIG - 26




FIG - 27




FIG. 28




FIG-29




FIG-30




FIG 31A




FIG 31B




FIG 31C

FIG 31D




FIG-32A






FIG-32B




Fig. 33a




FIG- 33B




FIG- 34





FIG-35




FIG- 36 A




FIG-36B




FIG - 37







FIG- 39B






FIG - 40




FIG. 41A




FIG. 41B




FIG. 42A




FIG. 42B




FIG-43





FIG 44D




FIG 45A




FIG 45B




FIG 46A




FIG 46B




FIG 47A




FIG 47B




FIG 47C




FIG 47D






FIG - 48




FIG- 49




FIG. 49A




FIG. 49B





FIG. 49-C









FIG- 51

52/84



FIG\_52






FIG 55A





FIG 55 B








FIG-57






FIG. 53




FIG- 60




FIG-61A

FIG-61B




FIG 62A




FIG 62B




FIG 62C




FIG 62D

62/84




FIG-63






FIG-64




FIG 65A




FIG 65B




FIG 65C




FIG-66




FIG 66A




FIG 66B




FIG 67




FIG 68




FIG 69A




FIG 69C




FIG 69B




FIG 70A




FIG 70B




FIG 71




FIG 72A




FIG 72B




FIG-73C




FIG-73B




FIG-73A




FIG - 74






FIG-75

72/84




Fig-76




FIG 77A



FIG 77B






Fig- 78



75/84




FIG-81




FIG-82




FIG 23




FIG 84




FIG. 84A




FIG 84-B






FIG 85




FIG 86




FIG 87A




FIG 87E




FIG 87C




FIG 88




FIG 29

84/84




FIG. 90A




FIG. 90B

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**